



GE  
Lighting

20900 - GE Blax® T5 - Facilities; Retail Display; Hospitality; Office;  
Restaurant; Warehouse

F50BXSPX41RS10PK

### Product Photo



### GENERAL CHARACTERISTICS

|                                 |  |
|---------------------------------|--|
| Base Type                       | Pin/Plug-In  |
| Mercury Content                 | 4 mg   |
| Rated Life Hours-nominal        | 20000 h  |
| Starting Temp (MIN) C-degrees   | 10 °C  |
| Base Description                | 4-Pin  |
| Mercury-Picogram per mean lm hr | 58.8   |
| Primary Application             | Facilities<br>Retail Display<br>Hospitality<br>Office<br>Restaurant<br>Warehouse |
| Product Technology              | Compact Fluorescent  |
| Base                            | 2G11   |
| Bulb Shape                      | R30  |

### PHOTOMETRIC CHARACTERISTICS

|                                |         |
|--------------------------------|---------|
| Mean Lumens nominal            | 3400 lm |
| Nominal Initial Lumen per Watt | 80      |
| Initial Lumens-nominal         | 4000 lm |
| Color Rendering Index-CRI      | 82      |
| Color Temperature              | 4100 K  |

### PRODUCT INFORMATION

|                                  |                  |
|----------------------------------|------------------|
| Product Code                     | 20900            |
| Description                      | F50BXSPX41RS10PK |
| Alternative Unit Of Measure      | Case             |
| Standard Package Quantity        | 10               |
| Ean UPC                          | 043168209007     |
| Standard Package GTIN            | 10043168209004   |
| No Of Items Per Sales Unit       | 1                |
| No Of Items Per Standard Package | 10               |
| Sales Unit                       | Unit             |
| UCC                              | 043168209007     |

### DIMENSIONS

|                             |         |
|-----------------------------|---------|
| Nominal Length              | 22.5 in |
| Bulb Max Overall Length-MOL | 22.5 in |

### ELECTRICAL CHARACTERISTICS

|                               |       |
|-------------------------------|-------|
| Equivalent Incandescent Watts | 200 W |
| Rated power (Watts)           | 50 W  |

### CAUTIONS & WARNINGS

#### Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

### NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).