


**4 IN. SQUARE WELDED BOXES - 1-1/2 IN. DEEP WITH ARMORED CABLE / METAL CLAD / FLEX CLAMPS****4 in. Square Box, 2-1/8 in. Deep - Welded with STAB-IT Connector
600V, 8" #12 Solid Copper Pigtail, UBS, M Bracket****A18**

Catalog #: 248MS

APPLICATIONS

RACO® STAB-IT boxes are great for any job where flexible armored cable is being used
RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

PRODUCT FEATURES

Designed for quick installation of flex, MC, MCI, MCI-A, AC, and HCF Cable
TKO® Knockouts offer greater flexibility with RACO patented combination 1/2" and 3/4" knockout
UBS Support - Welded to box, preset bend points to work with wall thickness 2-1/2" to 6"

UL LISTED

File E195978

CULUS

N/A

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL
"Fire Resistance Directory" or the UL website at www.ul.com

MSDS

[www.hubbell-rtb.com/certifications/Hubbell-RACO MSDS for Steel Boxes and Covers.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_Steel_Boxes_and_Covers.pdf)**FIRE RESISTANCE**

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System:	Armored Cable/Metal Clad/MCI-A/Flex
Color:	Gray
Country of Origin:	USA

CONFIGURATION

Cable Priouts:	4
Bracket Type:	M Bracket
Bracket Setback:	3/8 In.
Drawn or Welded:	Welded
Raised Ground:	No
Gangs:	2
Side Knockout(s):	(4) 1/2", (2) 1/2"-3/4" TKO
Bottom Knockouts(s):	(1) 1/2", (1) 1/2"-3/4" TKO

PRODUCT MEASUREMENTS

Depth:	2-1/8 In.
Cubic Inches (cm3):	30.3 (496.5)
Product Length (in.):	2.750
Product Width (in.):	5.860
Product Height (in.):	4.000

PACKAGING

Package Type:	Boxed
Minimum Pack Qty.:	25
Std. Pkg.:	25
Ship Carton Qty.:	25
Product UPC-A Labeled:	No
Ship Carton Length (in.):	20.875
Ship Carton Width (in.):	8.500
Ship Carton Height (in.):	9.000
Pallet Qty:	1375
UPC Number:	050169500798
I2of5:	50050169500793

