



T12 Recessed Double Contact

RAPID START LAMPS**High Output (800mA) Standard Rapid Start Lamps**

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life 3 Hours per start	CCT (K)	CRI	Approx Lumens Initial (Mean) 25°C/77°F	Notes
25	T12	18	15.91	Reces- sedDC	25303	F18T12/DSGN50/HO	30	9000	5000	90	850 (740)	ℓ,3,12, 13,17
35	T12	24	21.91	Reces- sedDC	25313	F24T12/CW/HO	30	9000	4200	60	1650 (1335)	ℓ,3,12, 13,17
					25314	F24T12/D/HO	30	9000	6500	76	1400 (1135)	ℓ,3,12, 13,17
42	T12	30	27.91	Reces- sedDC	25322	F30T12/CW/HO	30	9000	4200	60	2250 (1825)	ℓ,3,12, 13,17
45	T12	36	33.91	Reces- sedDC	25333	F36T12/CW/HO	30	9000	4200	60	2850 (2310)	ℓ,3,12, 13,17
					25332	F36T12/D/HO	30	9000	6500	76	2500 (2025)	ℓ,3,12, 13,17
55	T12	42	39.91	Reces- sedDC	25342	F42T12/CW/HO	30	9000	4200	60	3400 (2755)	ℓ,3,12, 13,17
					25343	F42T12/D/HO	30	9000	6500	76	3050 (2470)	ℓ,3,12, 13,17
60	T12	48	46.00	Reces- sedDC	25147	F48T12/WW/HO	30	12000	3000	52	4130 (3345)	ℓ,3,12, 13,17
					25154	F48T12/D35/HO	30	12000	3500	70	4250 (3825)	ℓ,3,12, 13,17
					25146	F48T12/CW/HO	30	12000	4200	60	4050 (3280)	ℓ,3,12, 13,17
					25122	F48T12/CW/HO/ECO	30	12000	4200	60	4050 (3280)	ℓ,3,12, 13,17
					25153	F48T12/DSGN50/HO	30	12000	5000	90	3050 (2470)	ℓ,3,12, 13,17
					25150	F48T12/D/HO	30	12000	6500	76	3600 (2915)	ℓ,3,12, 13,17
75	T12	60	57.91	Reces- sedDC	25128	F60T12/D35/HO	30	12000	3500	70	5600 (5040)	ℓ,3,12, 13,17
					25126	F60T12/CW/HO	30	12000	4200	60	5200 (4210)	ℓ,3,12, 13,17
					25120	F60T12/D/HO	30	12000	6500	76	4600 (3825)	ℓ,3,12, 13,17
80	T12	64	61.91	Reces- sedDC	25352	F64T12/CW/HO	30	12000	4200	60	5750 (4660)	ℓ,3,12, 13,17
					25353	F64T12/D/HO	30	12000	6500	76	4900 (3970)	ℓ,3,12, 13,17

For the current listing of available products and more complete product information, please visit us at www.sylvania.com. Specifications subject to change without notice.