




Topaz Specification Sheet

Description: Raintight compression type connector used to join EMT to a box or enclosure.

Standard Material: Steel

Standard Finish: Zinc Plated

Features: Concrete Tight and Raintight
Assembled with a Steel Locknut and Gasket



TOPAZ CAT#	A	B	C
651SRT	.689	.500	1.125
652SRT	.750	.500	1.375
653SRT	.846	.562	1.687
654SRT	1.687	1.012	2.062
655SRT	1.717	1.062	2.250
656SRT	1.875	1.125	2.750
657SRT	1.968	1.562	3.625
658SRT	2.689	1.562	4.250
659SRT	2.812	1.812	4.687
660SRT	2.812	1.812	5.187

651SiRT	.689	.500	1.125
652SiRT	.750	.500	1.375
653SiRT	.846	.562	1.687
654SiRT	1.687	1.012	2.062
655SiRT	1.717	1.062	2.250
656SiRT	1.875	1.125	2.750
657SiRT	1.968	1.562	3.625
658SiRT	2.689	1.562	4.250
659SiRT	2.812	1.812	4.687
660SiRT	2.812	1.812	5.187

TOPAZ CAT #	UPC#	SIZE	UNIT CTN	SHIP CASE	WT/ CASE
651SRT	83059	1/2"	25	250	30
652SRT	83060	3/4"	25	250	43
653SRT	83061	1"	10	100	25
654SRT	83062	1 1/4"	—	25	12
655SRT	83063	1 1/2"	—	20	12
656SRT	83064	2"	—	15	15
657SRT	83598	2 1/2"	—	12	19
658SRT	83599	3"	—	12	15
659SRT	83600	3 1/2"	—	5	16
660SRT	83659	4"	—	3	21

INSULATED THROAT

651SiRT	83006	1/2"	25	250	30
652SiRT	83007	3/4"	25	250	43
653SiRT	83008	1"	10	100	25
654SiRT	83009	1 1/4"	—	25	12
655SiRT	83010	1 1/2"	—	20	12
656SiRT	83011	2"	—	15	15
657SiRT	83512	2 1/2"	—	12	19
658SiRT	83513	3"	—	6	15
659SiRT	83614	3 1/2"	—	5	16
660SiRT	83615	4"	—	3	21



Approved by Quality Control: John Cavalieri



NEW YORK
925 Waverly Avenue
Holtville, NY 11742
800-666-2852
Fax: 800-333-3488

CALIFORNIA
225 Parkside Drive
San Fernando, CA 91340
888-551-2852
Fax: 888-690-2852

FLORIDA
2020 West 26th Street
Jacksonville, FL 32209
800-666-2852
Fax: 800-333-3488