



Topaz Specification Sheet


Description: Rigid Conduit Bodies, Malleable Iron LB Type

Standard Material: Malleable Iron

Standard Finish: Zinc Plated, Aluminum Enameled

Features: Tapered threaded hubs - NPT

Application: To provide access to conductors for pulling, splicing and maintenance



E195124

TOPAZ CAT #	A	B	C	Max No. Conductors	Internal Volume (in ³)
LB1M	4.56	2.06	1.31	---	4.5
LB2M	5.31	2.37	1.48	3 #6 AWG	7.5
LB3M	6.25	2.63	1.75	3 #4 AWG	12.5
LB4M	8.22	3.50	2.40	3 #2 AWG	32.3
LB5M	8.22	3.75	2.40	3 #1/0 AWG	35.3
LB6M	10.48	4.31	3.05	3 #4/0 AWG	73
LB7M	13.75	4.45	4.38	3-300 MCM	138
LB8M	13.75	4.45	4.38	3-350 MCM	170
LB9M	16.75	5.80	5.63	3-500 MCM	300
LB10M	16.75	5.80	5.63	3-500 MCM	328

TOPAZ CAT #	UPC#	SIZE	SHIP CASE	WT/ CASE
LB1M	20940	1/2"	10	7
LB2M	20950	3/4"	10	9
LB3M	20960	1"	5	6
LB4M	20970	1 1/4"	5	23
LB5M	20980	1 1/2"	10	26
LB6M	20990	2"	5	26
LB7M	21000	2 1/2"	1	10
LB8M	21010	3"	1	13
LB9M	21020	3 1/2"	1	22
LB10M	21030	4"	1	24

Approved by Topaz Quality Control & Engineering



NEW YORK
925 Waverly Avenue
Holtsville, NY 11742
800-666-2852
Fax: 800-333-3488

CALIFORNIA
225 Parkside Drive
San Fernando, CA 91340
888-551-2852
Fax: 888-690-2852

FLORIDA
2020 West 26th Street
Jacksonville, FL 32209
800-666-2852
Fax: 800-333-3488