




Topaz Specification Sheet

Description: Rigid Conduit Bodies with Cover and Gasket - Rigid T Type

Standard Material: Aluminum Die Cast Copper Free
Cover stamped steel
Gasket - Neoprene Rubber

Features: Tapered threaded hubs - NPT
Suitable for use in concrete.
Wet Location

Application: To provide access to conductors for pulling, slicing and maintenance



TOPAZ CAT #	A	B	C	Max No. Conductors
T1CG	4.720	1.370	1.330	1 #6AWG
T2CG	5.570	1.625	1.540	2 #6AWG
T3CG	6.460	1.900	1.740	3 #6AWG
T4CG	8.528	2.770	2.490	3 #2AWG
T5CG	8.528	2.770	2.490	3 #2AWG
T6CG	10.831	3.335	3.100	3 #2/0AWG
T7CG	13.500	4.060	5.825	3 #4/0AWG
T8CG	13.500	4.685	5.825	3 #250MCM
T9CG	15.937	5.450	7.060	3 #350MCM
T10CG	15.937	5.450	7.060	4 #350MCM

TOPAZ CAT #	UPC#	SIZE	UNIT CTN	SHIP CASE	WT/ CASE
T1CG	21731	1/2"	10	100	38
T2CG	21741	3/4"	10	50	30
T3CG	21751	1"	5	25	20
T4CG	21761	1 1/4"	2	10	19
T5CG	21771	1 1/2"	2	10	21
T6CG	21781	2"	—	2	5
T7CG	21791	2 1/2"	—	1	8
T8CG	21801	3"	—	1	8
T9CG	21811	3 1/2"	—	1	11
T10CG	21821	4"	—	1	11

Approved by Quality Control: John Cavalieri



NEW YORK
925 Waverly Avenue
Holtsville, NY 11742
800-666-2852
Fax: 800-333-3488

CALIFORNIA
225 Parkside Drive
San Fernando, CA 91340
888-551-2852
Fax: 888-690-2852

FLORIDA
2020 West 26th Street
Jacksonville, FL 32209
800-666-2852
Fax: 800-333-3488