



GE
Lighting

13767 - GE Daylight T12

F84T12D/HO 15PK

Product Photo



GENERAL CHARACTERISTICS

Base Description	Recessed Double Contact
Base Type	Pin/Plug-In
Mercury Content	90 mg
Mercury-Picogram per mean lm hr	1325.1
Starting Temp (MIN) C-degrees	-29 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	12000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	R17d
Bulb Shape	T12

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	5660 lm
Nominal Initial Lumen per Watt	65
Initial Lumens-nominal	6500 lm
Color Rendering Index-CRI	75
Color Temperature	6500 K

PRODUCT INFORMATION

Product Code	13767
Description	F84T12D/HO 15PK
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168137676
Standard Package GTIN	10043168137673
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168137676

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.59 in
Bulb Diameter (DIA) <Min>	1.41 in
Diameter	1.5 in
End of Base Pin to Pin	81.72 in
Nominal Length	84.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (rapid start) Min @ Temperature	430.00 V @ 10 °C
455.00 V @ -29 °C	Cathode Resistance Ratio - Rh/Rc (MIN)
4.250	Cathode Resistance Ratio - Rh/Rc (MAX)
6.500	Rated power (Watts)



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
- Turn power off before inspection installation or removal.



May 12, 2017 6:59:58 AM For additional information, visit www.gelighting.com