

14DUD320A | US2:14DUD320A



Non-reversing motor starter, Size 1, Three phase full voltage, Solid-state overload relay, OLRelay amp range 5.5-22a, 110 120/220 240VAC 60HZ coil, Non-combination type, Enclosure type 12, Dust/drip proof for indoors, Standard width enclosure

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Image similar

Product

Article Number (Market Facing Number)	14DUD320A US2:14DUD320A
Product Description	Non-reversing motor starter, Size 1, Three phase full voltage, Solid-state overload relay, OLRelay amp range 5.5-22a, 110 120/220 240VAC 60HZ coil, Non-combination type, Enclosure type 12, Dust/drip proof for indoors, Standard width enclosure

Product family	Ordering Data Overview
Product Lifecycle (PLM)	PM300:Active Product

Price data

Price Group	UMM
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : EAR99
Standard lead time ex-works	2 Day/Days
Net Weight (lb)	25.045 lb
Product Dimensions (W x L x H)	Not available
Packaging Dimension	Not available
Package size unit of measure	in
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	783087944992
Commodity Code	8536504000
LKZ_FDB/ CatalogID	CC-IC10
Product Group	5431
Country of origin	United States of America
RoHS Compliance	not available
Returnable	Yes
Obligation Category for taking back electrical and electronic equipment after use	No obligation to take back electrical and electronic equipment after use

Classifications

	Version	Classification
eClass	7.1	27-37-09-05
eClass	8	27-37-09-05
eClass	9	27-37-09-05
eClass	9.1	27-37-09-05
ETIM	5	EC001037
ETIM	6	EC001037
IDEA	4	4734
UNSPSC	15	39-12-15-21