




R14



R16




S11



T6.5



T8



T10



A21



BR30



R20



A19

GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life(hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
40	R14	Med	14819	●	40R14/RP	120	6	Reflector Mini Flood	C, C-9	1500	185		2.25
	R16	Med	14821	●	40R16/FL/RP	120	6	Reflector Mini Flood	C, C-9	1500			3.88
	S11	Intermediate	13595	●	40S11N	120	120	Clear Hi Intensity	C, C-7A	500	440	1.63	2.31
			13607	●	40S11N/BL	120	12	Clear Hi Intensity	C, C-7A	500	440	1.63	2.31
			13644	●	40S11N/BL/2/12	120	12	Clear Hi Intensity	C, C-7A	500	440	1.63	2.31
			13640	●	40S11N/NEO/BULK	120	6000	Neodymium doped Hi Intensity	C, C-7A	500		1.63	2.31
	T6.5	Intermediate	18096	●	40T6.5/2	120	60	Clear Appliance	C, C-8	1000	365		5.50
			18497	●	40T6.5/CL/BL/10PK	120	10	Clear Appliance	C, C-8	1000	365		5.50
			18152	●	40T6.5/CL/BL/6PK	120	6	Clear Appliance	C, C-8	1000	365		5.50
	T8	Intermediate	18358	●	40T8N/NEODYMIUM	120	6000	Neodymium Doped Appliance	B, C-7A	1000	300	1.31	2.63
	T10	Med	18650	●	40T10	120	60	Clear	B, C-8	1000	420		5.63
			18493	●	40T10/CL/BL/6PK	120	6	Clear	B, C-8	1000	420		5.63
			18652	●	40T10	130	60	Clear	B, C-8	1000	420		5.63
			18494	●	40T10/IF/BL/6PK	120	6	Inside Frost	B, C-8	1000	415		5.63
			18669	●	40T10/IF	130	60	Inside Frost	B, C-8	1000	415		5.63
45 95 140	A21	3 CONTACT Med	18048	●	45/140A21/W/ES/RP	120	12	Soft White 3-way Energy Saver	C, CC-8	1200	540lm 1300lm 1840lm	3.38	5.31
45	BR30	Med	15103	●	45BR30/FL/RP	120	6	Reflector Flood	C, CC-6	2000	350lm 170 cd 60°		5.38
	R20	Med	15677	●	45R20/DAY/1/6/RP	120	6	Daylight Reflector	C, C-9	2000	215lm 360 cd 45°		3.94
			15697	●	45R20	120	60	Reflector Flood	C, C-9	2000	295lm 490 cd 45°		3.94
			14997	●	45R20/RP/2/12	120	12	Reflector Flood	C, C-9	2000	295lm 490 cd 45°		3.94
			15670	●	45R20/RP	120	6	Reflector Flood	C, C-9	2000	295lm 490 cd 45°		3.94
			15699	●	45R20	130	60	Reflector Flood	C, C-9	2000	490 cd 45°		3.94
			<i>@ 120_volts, approximate 40 watts, 220 lumens, 5000 hours.</i>										
			15676	●	45R20/CVP	130	6	Reflector Flood	C, C-9	2000	490 cd 45°		3.94
			<i>@ 120_volts, approximate 40 watts, 220 lumens, 5000 hours.</i>										
	Med Brass		15698	●	45R20/DL/RP	120	6	Double Life Reflector Flood	C, C-9	4000	260 430 cd 45°		3.94
50	A19	Med	11096	●	50A/RS/4/144/RP	120	144	Inside Frost Rough Service	C	1000	510		
			14070	●	50A/RS/2/RP	120	24	Inside Frost Rough Service	C	1000	510		
			11393	●	50A/RS	250	120	Inside Frost Rough Service	C, C-22	1000	450	2.50	4.44