

18/4 RISER RATED, UNSHIELDED FIRE ALARM CABLE




18 AWG 4 SOLID CONDUCTORS

Ratings FPLR, CL3R, FT4
Approvals ETL Listed

Construction

Conductor 18 AWG Solid Bare Copper
Conductor Count 4
Insulation Riser PVC (0.011" nom.)
Insulation Colors Black, Red, Green, Yellow
Lay Length 6.00" nom.
Shielding N/A
Rip Cord Yes
Jacket PVC (0.015"nom.)
Overall Diameter 0.159" nom.
Print Legend ADI PRO P/N RN-200XXXX
OXYGEN FREE 4C18 3180662 (ETL)US
FPLR 75C ROHS CL3R
FT4 LOT#XXXX MMDDYY XXXXFT



Properties

Operating Voltage 300 Volts max.
DC Resistance 6.52 Ohms/1000'at 20°C
Capacitance 19.6 pF/ft.nom.
Temperature Wire maintains flexibility between -20°C/-4°F to 75°C/167°F. Exposure below 0°C/32°F may cause PVC jacket to be brittle or crack if impacted or bent.
Flame Rating UL1666(Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes
Country of Origin China

PART#	COLOR	LENGTH	BOX
RN-2008106	Red	1000Ft.	Express Box
RN-2002506	Red	500Ft.	Express Box



For more information contact
your ADI Sales person or visit
adiglobal.com/adiexclusivebrands