

16/2 RISER RATED, UNSHIELDED FIRE ALARM CABLE

ADI
PRO

16 AWG 2 SOLID CONDUCTORS

Ratings
Approvals

FPLR, CL3R, FT4
ETL Listed

Construction

Conductor 16 AWG Solid Bare Copper
Conductor Count 2
Insulation Riser PVC (0.011" nom.)
Insulation Colors Black, Red
Lay Length 2" nom
Shielding N/A
Rip Cord Yes
Jacket PVC (0.017"nom.)
Overall Diameter 0.162" nom.

Print Legend

ADI PRO P/N RN-20XXXX
OXYGEN FREE 2C16 3180662 (ETL)US
FPLR 75C ROHS CL3R FT4 LOT#XXXX
MMDDYY XXXXFT



Properties

Operating Voltage 300 Volts max.
DC Resistance 4.1 Ohms/1000'at 20°C
Capacitance 21.1 pF/ft.nom.
Temperature Wire maintains flexibility between -20°C/-4°F to 75°C/167°F. Exposure below 0°C/32°F may cause PVC jacket to be brittle or crack if impacted or bent.

Flame Rating UL 1666 (Riser);
CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes
Country of Origin China

PART#	COLOR	LENGTH	BOX
RN-2015506	Red	1000Ft.	Express Box
RN-2011506	Red	500Ft.	Express Box



For more information contact
your ADI Sales person or visit
adiglobal.com/adiexclusivebrands