

16/2 STRANDED RISER SPEAKER CABLE, UNSHIELDED



16 AWG 2 Stranded Conductors

Ratings
Approvals

CMR, CL3R, FT4
ETL Listed

Construction

Conductor
Conductor Count
Insulation
Insulation Colors
Lay Length
Shielding
Rip Cord
Jacket
Overall Diameter

16 AWG Oxygen-Free Bare Copper, 26-Stranded
2
Polypropylene (0.008" nom.)
Red, White
24" nom.
N/A
Yes
PVC (0.025" nom.)
0.180" nom.

Print Legend

ADI PRO P/N RN-500XXXX OXYGEN
FREE 2C16 3180662 (ETL)US CL3R
ROHS C(ETL)US CMR FT4 1000FT



Properties

Operating Voltage
DC Resistance
Capacitance
Impedance
Temperature
Flame Rating

300 Volts max.
4.19Ohms/1000' at 20°C
22.5pF/ft. nom.
68Ohms nom.
-20°C to 60°C
UL 1666 (Riser);
CSA C22.2 No. 2556 (FT4)

RoHS Compliant
Country of Origin

Yes
CHINA

PART#	COLOR	LENGTH	BOX
RN-5000101	WHITE	1000FT	EXPRESS BOX
RN-5000108	BLACK	1000FT	EXPRESS BOX
RN-5000501	WHITE	500FT	EXPRESS BOX
RN-5001503	GREEN	500FT	EXPRESS BOX
RN-5001502	BLUE	500FT	EXPRESS BOX



For more information contact
your ADI Sales person or visit
adiglobal.com/adiexclusivebrands