

# 16/4 STRANDED RISER SPEAKER CABLE, UNSHIELDED

# ADI PRO

## 16 AWG 4 Stranded Conductors

Ratings CMR, CL3R, FT4  
Approvals ETL Listed

### Construction

Conductor 16 AWG Oxygen-Free Bare Copper, 26-Stranded  
Conductor Count 4  
Insulation Polypropylene (0.008" nom.)  
Insulation Colors Red, White, Green, Blue  
Lay Length 24" nom.  
Shielding N/A  
Rip Cord Yes  
Jacket PVC (0.016" nom.)  
Overall Diameter 0.214" nom.

Print Legend ADI PRO P/N RN-500XXXX OXYGEN  
FREE 4C16 3180662(ETL)US CL3  
RROHS C(ETL)US CMR FT4 500FT



### Properties

Operating Voltage 300 Volts max.  
DC Resistance 4.19Ohms/1000' at 20°C  
Capacitance 22.5pF/ft. nom.  
Impedance 68Ohms nom.  
Temperature -20°C to 60°C  
Flame Rating UL 1666 (Riser);  
CSA C22.2 No. 2556 (FT4)  
RoHS Compliant Yes  
Country of Origin CHINA

PART#	COLOR	LENGTH	BOX
RN-5002501	WHITE	500FT	EXPRESS BOX



For more information contact  
your ADI Sales person or visit  
[adiglobal.com/adiexclusivebrands](http://adiglobal.com/adiexclusivebrands)