

LED Suspended High Bay/Low Bay

INDUSTRIALS

FEATURES

- Quick and simple aircraft cable hanging system or pendant mount bracket available
- Long-life, 60,000 hour LEDs at L80 reduce life cycle maintenance costs
- Four LED color choices and 83 CRI
- Diffuse Wrap Lens available
- Utilizes TIR directional linear optics for optimal aisle lighting performance
- Available in narrow or wide distribution
- Fixed output or 0-10V dimming drivers ; 1% dimming optional
- Easy access to LED boards and drivers
- CSA listed and suitable for damp locations
- Available with factory installed On/Off or Dimming Occupancy Sensors with wide or aisle lens option
- Design Lights Consortium (DLC) qualified
- Five year warranty



ORDERING INFORMATION

LWS					
MODEL	LUMEN OUTPUT	DISTRIBUTION	VOLTAGE	OPTIONS	
LWS LED Suspended High Bay	ML Medium Lumen HL High Lumen VL Very High Lumen XL Xtra High Lumen See Product Availability Table below.	AC Aisle-Clear Optics AD Aisle-Diffuse Optics W Wide (SFA option recommended with W distribution)	U 120V-277V 347 347V 480 480V	C6TL15 6' Cord and Twist-Lock™ Plug 15A (Add Voltage: 1=120, 2=277) C6TL20 6' Cord and Twist-Lock™ Plug 20A (Add Voltage 1=120, 2=277) C6P151 6' Cord and Straight Blade Plug 15A (Add Voltage: 1=120V, 2=277V) F3CX 3-Conductor Cord (add length for X: 5=5', 10=10', 15=15') F4CX 4-Conductor Cord (add length for X: 5=5', 10=10', 15=15') F5CX 5-Conductor Cord (add length for X: 5=5', 10=10', 15=15') ELL14 Emergency Battery Pack Installed, 1400 Lumens ^{2,3} SFA Smooth Frosted Acrylic Wrap Lens GLR Fast Blow Fuse PM Pendant Mounting Bracket 3/4" (pendant not included) OS1360 Factory Installed Occupancy/Daylight, Sensor, 1-relay, 360° lens 120/277 OS2360 Factory Installed Occupancy/Daylight, Sensor, 2-relay, 360° lens 120/277 OS1A Factory Installed Occupancy/Daylight Sensor, 1-relay, Aisle lens, 120/277 OS2A Factory Installed Occupancy/Daylight Sensor, 2-relay, Aisle lens, 120/277 ODS1360 Factory Installed Dimming Occupancy/Daylight Sensor, 1-relay, 360° lens 120/277 ODS1A Factory Installed Dimming Occupancy/Daylight Sensor, 1-relay, Aisle lens 120/277	
	COLOR TEMP		DRIVER		
	30 3000K 35 3500K 40 4000K 50 5000K		E Fixed Output ED 0-10V Dimming ED1 0-10V Dimming to 1% ¹		

ACCESSORIES (ORDER SEPARATELY)

- LWSQM5** Aircraft Cable 5' (Pair)
- LWSQM10** Aircraft Cable 10' (Pair)
- C6TL15-120** Cord & Plug Kit, 6 ft, Twist Lock NEMA L5-15P, 15 amp, 120V, White
- C6TL15-277** Cord & Plug Kit, 6 ft, Twist Lock NEMA L7-15P, 15 amp, 277V, White
- C6P15-120** Cord & Plug Kit, 6 ft, Straight Blade NEMA 5-15P, 15 amp, 120V, White
- LWS-WG** Wire Guard, white, field installed

¹ED1 available with ML and HL only
²Not available in 347V or 480V
³For compatibility with Dual-Lite LiteGear® inverters, contact Hubbell Lighting Representative

PRODUCT AVAILABILITY

OUTPUT	NOMINAL LUMENS	WATTS	LPW	AMBIENT
ML	9,750-11,115	87	124	55°C
HL	11,050-14,540	110	125	40°C
VL	13,780-16,910	146	119	40°C
XL	15,300-20,400	163	118	40°C

