



FLUSH BOLTS



1555
Metal Doors



1557
Wood Doors

NUMBER	SIZE	ANSI A156.16	MATERIAL
1555	Face Plate: 1" x 6 3/4"	L14251	Cast Brass
	Strike: 15/16" x 2 1/4"		
	Guide: 1" x 2"		
1557	Face Plate: 1" x 6 3/4"	L04261	Cast Brass
	Strike: 15/16" x 2 1/4"		

SHELF PACK: 10

Box Pack

FASTENERS: (1555) 4 ea. #8 x 1 1/2" Combo Screw, 4 ea. #8 x 3/4" Combo Screw
(1557) 7 ea. #8 x 3/4" Combo Screw

FEATURES: (1555) • Fits ANSI Door & Frame Prep.
• 3/4" Bolt Throw, 3/4" Rod Backset
• 12" Rod length
• 1 1/2" Adjustable Bolt Head

FEATURES: (1557) • 3/4" Bolt Throw, 3/4" Backset
• Door strength maintained by corner reinforcement plate

FINISHES: 605, 606, 612, 613, 625, 626

OPTIONS: (1555) Longer rod options available
Works w/1570 Dust Proof Strike

AUTOMATIC FLUSH BOLTS



1560
Metal Doors

NUMBER	SIZE	ANSI A156.3	MATERIAL
1560	Face Plate: 1" x 6 3/4"	Type 25	Brass
	Strike: 15/16" x 2 1/4"		Cast Brass
	Guide: 1" x 1 7/8"		Cast Brass
	Door Strike: 1 3/4" x 1 3/4"		Cast Brass

SHELF PACK: 10

Box Pack

FASTENERS: 8 ea. #8 x 3/4" Combo Screw, 2 ea. #8 x 3/8" MS

FEATURES: • Non handed
• Conforms to UL, IOC and UBC 7-2-1997
• For Fire Rated Metal Doors labeled A, B, C, D & E
• Sold in pairs
• Fits standard ANSI prep for metal doors
• Requires only 5 lbs. of force meeting ADA regulations
• 1" vertical adjustment for bolts

FINISHES: 605, 613, 626

OPTION: Works w/1570 Dust Proof Strike