


Strength By Design

Designed to withstand automotive vehicle weight without moving in concrete.

Meets Load Rating B*

HOT PRODUCTS

- Grates snap in and out, no screws required.
- Grates are concave to more efficiently trap & transfer water.



- Channel lengths are interlocking with a secure built-in joining system.

- Anti-floatation feet secure Channels in back fill or concrete.
- Cross braced ribs are designed into the body for strength and rigidity.

Bottom outlet in every Channel.

- Built in bottom outlet in each Channel is easily cut out with a utility knife and accommodates 4" sewer and drain pipes. The leaf guard also easily fits into the bottom outlet.

90° Corner
FSD-90CGG



90° Corner allows left or right hand extension of the Storm Drain

End Cap
FSD-EC



End Caps just slide into Storm Drain

Leaf Guard
FSD-LG



Leaf Guard prevents debris from going down drain pipe


End Outlet
FSD-EO



End Outlet accommodates 3" & 4" sewer and drain pipe OR 3" & 4" Sch. 40 fitting hub



Simple accessory attachment.



- The Storm Drain 90° Corner, End Cap and End Outlet just slide into the female end of the Channels. They also each have tabs to fit into the male end of the Channels or the cut to length end of the Channels.

No clips or screws required to assemble.

** **CLASS B:** Loads of 61-175 psi. Recommended for medium-duty pneumatic tire traffic, autos and light trucks at speeds less than 20 mph.*