

Fence Fabric Clamps

Part No.	Conductor Size (AWG)	Torque Rating (in./lb.)	Box Qty.	Approx. Box Wt. (lbs.)
FGC8	#8	67	25	5
FGC6	#6	67	25	5
FGC4	#4	67	25	5
FGC2	#2	67	25	5
FGC1/0	1/0	67	10	3
FGC2/0	2/0	67	10	3
FGC2-3/0*	#2 & 3/0	67	10	3
FGC2-4/0**	#2 & 4/0	67	10	3



cUL US Listed 467

*Accepts a #2 AWG and/or 3/0 AWG conductor.

**Accepts a #2 AWG and/or 4/0 AWG conductor.

Tamper Proof

Part No.	Conductor Size (AWG)	Torque Rating (in./lb.)	Box Qty.	Approx. Box Wt. (lbs.)
FGC8TP	#8	96	25	5
FGC6TP	#6	96	25	5
FGC4TP	#4	96	25	5
FGC2TP	#2	96	25	5
FGC26TP	#2 & #6	96	25	5
FGC2/0TP	2/0	96	10	3
FGC2-4/0TP**	#2 & 4/0	96	10	3



cUL US Listed 467

**Accepts a #2 AWG and/or 4/0 AWG conductor.

NOTES:

- Unique design allows clamp to form connections at any angle.
- Designed for 9 thru 6 gauge(0.148" - 0.192") fence fabric.
- Please contact factory for applications outside of listed ranges.
- Specific uses include connection to both fence fabric and barbed wire.
- The conductor maintains a direct path to ground while connected to an object that is parallel, perpendicular or any degree in between.
- Electro tin plated brass clamp includes stainless steel hardware.
- Allows for use with most metallic surfaces including galvanized.

Fence Bonding & Grounding Systems

Fence bonding & grounding systems are designed to provide protection against dangerous "touch" potentials. The fence fabric ground clamp is an integral component of this personnel safety system.

