Stainless Steel Venting for SV and DV Models SV DV



The Line-up: 3", 4" & 5"

Noritz N-Vent is available in three sizes: 3", 4" and 5". N-Vent is UL-Listed and ideal for tankless installations such as direct vent, horizontal, vertical and outdoor applications. Adjustable venting offers flexibility for different vent runs.

Easy Connection

Noritz supplies easy-to-connect venting componentsthe most simple in the industry to install. Unlike other brands, there's no need to tighten as the Noritz N-Vent



has a Quick-Snap feature that allows for an easy connection while forming a tight seal. In addition, Noritz offers a special appliance adapter that connects N-Vent components to other manufacturers' tankless heaters or boilers.

UL Listed



Noritz N-Vent is UL approved Category III venting. Underwriter's Laboratories (UL), an independent not-for-profit product safety testing and certification organization is one of the most recognized safety agencies in the world. N-Vent is approved for tankless and boiler stainless steel exhaust installations at a fraction of the industry standard cost.


The N-Vent Termination Kits

N-Vent Horizontal Vent Kit

VK4-H-*

Specifications & Features

- Stainless Steel
- 4" Diameter
- Flexibility for different wall thicknesses
- Easy installation
- Professional appearance



Part Number Based on Wall Thickness as Follows:

Wall Thickness	*Venting Kit Number					
4.1"- 7.4"	VK4-H-8-1					
7.4"- 14"	VK4-H-14-1					

Horizontal Kit Contains:


Description	Part Number	Quantity
Wall Thimble with Built-in Hood Termination	WT4-H-#-1 (# Based on wall thickness)	1
90 Degree Elbow	VP4-90ELB)	1
7"- 9.4" Adjustable Vent	VP4-9.4ADJ	1

N-Vent Vertical Vent Kit

VK4-V1

Specifications & Features

- Stainless Steel
- 4" Diameter
- Easy installation
- Professional appearance



Vertical Kit Contains:

Description	Part Number	Quantity		
Drain Tee	DT4	1		
90 Degree Elbow	VP4-90ELB	2		
Firestop	FS4	1		
Support Clamp	SC4	1		
Roof Jack	RJ4	1		
Storm Collar Pipe	SCP4	1		
Rain Cap	RC4	1		
9"- 13.4" Adjustable Vent	VP4-13.4ADJ	1		

Stainless Steel Venting for SV and DV Models SV DV

Part Name	Туре	Description	Drawing	Size	Dimensions (inches)		Part Number	Qty/Box		
				3	3.0	L 2		5.9	VT3-S	6
VENT TERMINATION Horizontal 45 Degree Birdscreen	Straight Birdscreen		4	4.0	_		6.2	VT4-S	6	
			5	5.0			7.9	VT5-S	6	
	45 Degree Birdscreen		4	4.0	4.0 2.1		4.0	VT4-S45	6	
			5	5.0		\perp	5.4	VT5-S45	6	
				3	D 2.0	L1	L	D1	VT2 CII	6
	Hood	D1 D	4	3.0 4.0	2.1	5.5 6.1	3.2 7.4	VT3-SH VT4-SH	6	
				5	5.0	2.8	6.6	7.4	VT5-SH	6
	Horizontal		<u></u>		3.0	2.0	0.0	/	713 311	
VENT TERMINATION		Louver	D1 D	4	4.0	2.1	3.2	7.4	VT4-SL	6
				5	5.0	2.8	3.7	7.4	VT5-SL	6
			Di	3	3.0	2.0	6.8	6.3	RC3	6
	Vertical	Rain Cap		4	4.0	2.0	6.6	7.8	RC4	6
			L1 D	5	5.0	2.0	7.2	11.0	RC5	6
						L1		L		
	Horizontal	Drain Tee	D	3	3.0	2.0	7	.1	DT3	6
	TIOTIZOTICAL	Drain lee	3/8"	4	4.0	2.1	7.2		DT4	6
CONDENSATION				5	5.0	2.7	8	.0	DT5	6
DRAIN			L1 D	3	3.0	2.0	5	.1	DT3-V	6
	Vertical	Vertical Drain Tee	L	4	4.0	2.1	5	.1	DT4-V	6
				5	5.0	2.7	6	.2	DT5-V	6
			H Roof Jack		В	Н		C		
		Flat Roof Flashing		4	5.3	11.5	17	7.0	FRF4	6
				5	6.3	11.5	18	3.0	FRF5	6
			B 30	3	5.0	6.0		5.0	ARF3	1
A	Angled Roof Flashing	H	4	6.0	6.0	17	7.0	ARF4	1	
			c c	5	7.0	6.0	18	3.0	ARF5	1
ROOF PIECE Roof Jack		H solutions	3	4.0	18.0			RJ3	6	
	Roof Jack		4	5.0	18.0			RJ4	6	
		<u>B</u>	5	6.0	18.0			RJ5	6	
					D	Α	l	1		
Storm Collar Pipe	Storm Collar Pipe	Pipe Guide	4	4.0	7.8	23	3.6	SCP4	1	
			5	5.0	8.9	25	5.2	SCP5	1	
Storr	Storm Collar	A	3	3.0	7.8	3	.0	SCR3	6	
	Statil Collab	D	4	4.0	7.9	4	.0	SCR4	6	