

Eaton JM60030-3MW14

Catalog Number: JM60030-3MW14

Eaton Bussmann series JM modular fuse block, Multi-wire load-side lug, 30 A, 3-P, 120 °C, 50 lb-in Max, Class J, Black, Box lug, 200 kAIC, 75 °C, DIN rail|Panel, 600 V



General specifications

Product Name	Catalog Number
Eaton Bussmann series JM modular fuse block	JM60030-3MW14
	UPC
	051712620581
Product Length/Depth	Product Height
3.4 in	2.3 in
Product Width	Product Weight
3.3 in	0.475 lb
Warranty	Compliances
Not Applicable	RoHS Compliant
Certifications	
ARO	
European Pressure Equipment Directive (PED) 97 /23 EC	

Electrical rating

Amperage Rating

30 A

Impulse withstand voltage

200 kA RMS symmetrical

Interrupt rating

200 kAIC

Short-circuit rating

200 kA RMS symmetrical

Torque rating

50 lb-in maximum

Voltage rating

600 V

Physical details

Color

Black

Conductor material rated for

Both

Conductor temperature rating

75 °C

Conductor type

Stranded

Fuse type

Class J

Number of Poles

Three-pole

Operating temperature - max

120 °C

Operating temperature - min

120 °C

General information

Connection

Box lug

Mounting method

DIN rail

Panel

Special features

Multi-Wire Load-Side Lug

Resources

Catalogs

[JM60030-3MW14~3POLE J 600V30A PDFB 1-4](#)

[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - JM60030-3MW14](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia