

IT'S TIME TO DEMAND MORE

**Simple to install,
Simple to operate.
Simply the best.**

The Grundfos ALPHA will change the way you view circulators. With its permanent magnet motor design, this energy efficient circulator reduces power consumption by 50% or more. The unique patented AUTOADAPT™ feature controls pump performance automatically within defined performance range, ensuring lowest possible energy consumption without sacrificing comfort.

For installation, you also have the flexibility to use either our unique ALPHA Plug with line cord or the ALPHA with terminal box for conduit connection applications. The choice is yours.



be
think
innovate

GRUNDFOS 

THE UNIQUE FEATURES OF THE GRUNDFOS ALPHA™



Unique ALPHA Plug
with line cord



Terminal box for
conduit connection
applications



Large display shows
current energy
consumption in Watts



Large display shows
estimated flow in
gallons per minute



A one button, easy-
to-use interface



Nut capture



Compact design



Stainless steel and
cast iron pump
housing available



Integrated check-valve
(optional)



QR code
Scan with your smart
device to learn more
about ALPHA.



Technical Data:

Flow Range: 0 to 21 GPM

Head Range: 0 to 19 Feet

Motor: 1X115V

Min. Fluid Temperature: 36°F (2°C)


Max. Fluid Temperature: 230°F (110°C)

Max. Working Pressure: 150 PSI

Watts: 5-45W

Amps: 0.65A


Performance Curve:



Product Offering:

Model	Description	Part Number
ALPHA 15-55F	Cast iron flange with terminal box	59896877
ALPHA 15-55FR	Cast iron rotated flange with terminal box	59896878
ALPHA 15-55SF	Stainless flange with terminal box	59896879
ALPHA 15-55F/LC	Cast iron flange with line cord	59896832
ALPHA 15-55FR/LC	Cast iron rotated flange with line cord	59896833
ALPHA 15-55SF/LC	Stainless flange with line cord	59896834
	Service Kit - Line cord	91130247
	Service Kit - Terminal box	91130312

Dimensional Drawing:



A	B	C	D	E	F	G	H	I	J	K
6-1/2	6-3/16	4-15/16	3-13/16	2-3/8	3-7/16	4-1/8	5-3/8	6-11/16	5-1/4	6-1/2

At Grundfos, we believe in making the complicated seem simple and innovative technology intuitive. Bringing more flexibility and ease of use to your workflow, AUTOADAPT technology is revolutionary to the market. As the ideal choice for more than 80% of systems, AUTOADAPT will continuously search for the lowest possible head to meet system requirements and find the setting that provides optimal comfort with minimal energy consumption.

You can also go online and explore our Modern Comfort site for all your domestic buildings needs. Visit:

moderncomfort.grundfos.us



L-AL-SL-001 Rev. 04-13

GRUNDFOS Kansas City
17100 West 118th Terrace
Olathe, Kansas 66061
Phone: (913) 227-3400
Fax: (913) 227-3500

www.grundfos.us

GRUNDFOS Canada
2941 Brighton Road
Oakville, Ontario
L6H 6C9
Phone: (905) 829-9533
Fax: (905) 829-9512

www.grundfos.ca

GRUNDFOS Mexico
Boulevard TLC No. 15
Parque Industrial Stiva Aeropuerto
C.P. 66600 Apodaca, N.L. Mexico
Phone: 011-52-81-8144 4000
Fax: 011-52-81-8144 4010

www.grundfos.mx

GRUNDFOS 