



# 345 MHZ SENSORS (cont'd)

## 2GIG-DW10-345

### Thin Door/Window Contact

- For narrow applications, sensor is only 3/4" wide
- Fully supervised
- Rare earth magnet
- Supports internal and external contacts
- Can be used for 2 zones of protection
- Lithium battery
- ETL listed



also available in 120 pc. bulk packs: 2GIG-DW10-120PK

## 2GIG-DW20R-345

### Recessed Door Contact

- Compact size, only 2-1/2" long
- Fully supervised
- Rare earth magnet
- Lithium battery
- ETL listed

also available in 120 pc. bulk packs: 2GIG-DW20R-120PK



## 2GIG-DW40-345

### Bypass Door/Window Contact

- Bypass locally with integrated button
- Micro-sized sensor
- Logs bypass event in System History
- Fully supervised
- Lithium battery
- ETL listed



## 2GIG-KEY2-345

### 4-Button Key Ring Remote

- Arms system in Stay or Away Mode
- Disarms system
- Auxiliary output and emergency functions
- Lithium battery
- ETL listed



## 2GIG-TILT1-345

### Wireless Tilt Sensor

- Sensor transmits alert when tipped 45° off vertical
- Restore signal sent when sensor returned to less than 45°
- Requires Firmware Version 1.14 or later for GC2 panel and 3.1 or later for GC3
- Long life lithium battery included
- Screw, adhesive mount hardware included



## 2GIG-DBELL1-345

### Wireless Doorbell

- White UV-resistant plastic
- Surface mount
- 350 ft. range (open air)
- 11 selectable chimes
- Doorbell can illuminate
- Receive text/email from remote services provider if/when doorbell engaged
- Battery or low voltage for power
- Low battery indicator
- Battery included
- Weatherproof seal included



## 2GIG-PANIC1-345

### Panic Button Remote

- For triggering emergency alarm
- Small and lightweight
- 5-second button lockout
- Lithium battery
- ETL listed



## 2GIG-PIR1-345

### Passive Infrared Motion Detector

- Dual element sensor with 50' x 50' range
- 45 lb. pet immune
- 90-degree look down
- Lithium battery
- ETL listed



## 2GIG-FT1-345

### Flood and Temperature Sensor

- Detects standing water that reaches the sensor probe and notifies the panel
- Sends trouble alert to the panel when the ambient temperature exceeds 84 deg. F
- Sends trouble alert to the panel when the ambient temperature falls below 42 deg. F
- Ships with long life lithium battery life (typical battery life of 5 years)
- ETL listed
- Requires Firmware Version 1.14 or later for GC2 panel and 3.1 or later for GC3



## 2GIG-F1-345

### Fall Detector Pendant

- For triggering emergency alarm
- Multi-axes sensor intelligence recognizes most falls
- 3D sensing is designed to send an alert when a fall is detected
- IPX7 water resistant



## 2GIG-PHB1-345

### Personal Help Button Pendant-Wristband

- For triggering emergency alarm
- Convertible model with option to wear it as a pendant or on the wrist
- IPX7 water resistant

