



FPS-MPP1AJJ | 1469374
Fiber Optic Splitter, 1 x 32, SC/APC

Product Classification

Product Type	Splitter module
Regional Availability	North America
Product Series	FPS

Body Features

Color	Yellow
-------	--------

Configuration Features

Number of Splitter Slots	1
Output Connector/Adapter	SC angled polish
Splitter Style	Mini plug-and-play (PNP)
Splitter/Tap Distribution	1 x 32 Splitter

Electrical Characteristics

PDL	0.3 dB
Uniformity	1.3 dB

Operation/Application

For Use With	54" (137cm) FDH 3000 Cabinet
--------------	------------------------------

Other

Comment	Allows pass-through of up to 2 fibers per splitter.
---------	---

Packaging Features

Includes	Reversible Dust Cap
----------	---------------------

Product Type Features

Input Connector	SC Angled Polish
-----------------	------------------

Signal Characteristics

Directivity (Min)	60.000 dB
Loss (Max)	16.7 dB
Loss (Typical)	16.5 dB
Operating Wavelength	1260 – 1635 nm
Return Loss (Min)	55 dB

FPS-MPP1AJJ | 1469374

Usage Conditions

Operating Temperature -55 – 85 °C | -67 – 185 °F

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant