

INNOVATION FOR ANY PEX CONNECTION

**NEW SPACE-SAVING
WEBSTONE EXCLUSIVES**

**PRESS × PEX
TRANSITION UNIONS**

**NEW
PRESS × PEX
TRANSITION
FITTINGS**

- Lead-free forged DZR brass construction
- Eliminates multiple fittings and adapters
- Saves space and eliminates leak paths
- Compatible with popular press tools
- Items in sizes 1/2" – 2"

**PEX × PEX × PRESS
TRANSITION TEES**
with bullhead
sizes available

**PRESS × PRESS × PEX
TRANSITION TEES**
with reducing
sizes available

FOR ANY PEX CONNECTION

**F1807 CRIMP
OR CLAMP**



**F1960 COLD
EXPANSION**



Webstone®
a brand of **NIBCO®**

**VALVE INNOVATION
INSTALLATION SOLUTIONS**

webstonevalves.com/PEX



WARNING: Cancer and Reproductive
Harm - www.P65Warnings.ca.gov

LEAD-FREE: Weighted average lead content ≤ 0.25%

INNOVATION FOR ANY PEX CONNECTION

WEBSTONE EXCLUSIVES FOR F1807 & F1960 PEX

**PEX × PEX × PRESS
TRANSITION TEES**
with bullhead
sizes available



FORGED DZR BRASS TRANSITION TEE

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372 NSF/ANSI 14

SIZE	ITEM#	CTN/CASE	CASE WT
F1960 PEX × F1960 PEX × Press 250 PSI CWP Max/250°F Max			
1/2"	H-36852W	25/100	21
1/2" × 1/2" × 3/4"	H-36852W-BH	20/80	21
3/4"	H-36853W	20/80	29
3/4" × 3/4" × 1"	H-36853W-BH	16/64	29
1"	H-36854W	20/80	49
1 1/4"	H-36855W	6/24	28
1 1/2"	H-36856W	2/8	12
2"	H-36857W	2/8	29
F1807 PEX × F1807 PEX × Press 250 PSI CWP Max/250°F Max			
1/2"	H-16852W	25/100	18
1/2" × 1/2" × 3/4"	H-16852W-BH	20/80	20
3/4"	H-16853W	20/80	26
3/4" × 3/4" × 1"	H-16853W-BH	16/64	27
1"	H-16854W	20/80	42
1 1/4"	H-16855W	6/24	21

NEW PRESS × PEX TRANSITION FITTINGS

- Lead-free DZR brass construction
- Eliminates multiple fittings and adapters
- Saves space and eliminates leak paths
- Compatible with popular press tools
- Items in sizes 1/2" - 2"

**PRESS × PRESS × PEX
TRANSITION TEES**
with reducing sizes available

**PRESS × PEX
TRANSITION UNIONS**



FORGED DZR BRASS TRANSITION TEE

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372 NSF/ANSI 14

SIZE	ITEM#	CTN/CASE	CASE WT
Press × Press × F1960 PEX 250 PSI CWP Max/250°F Max			
1/2"	H-86352W	25/100	18
3/4"	H-86353W	20/80	27
3/4" × 3/4" × 1/2"	H-86353W-R	20/80	22
1"	H-86354W	20/80	45
1" × 1" × 3/4"	H-86354W-R	20/80	37
1 1/4"	H-86355W	4/16	16
1 1/2"	H-86356W	2/8	11
2"	H-86357W	2/8	24
Press × Press × F1807 PEX 250 PSI CWP Max/250°F Max			
1/2"	H-86152W	25/100	17
3/4"	H-86153W	20/80	25
3/4" × 3/4" × 1/2"	H-86153W-R	20/80	21
1"	H-86154W	20/80	40
1" × 1" × 3/4"	H-86154W-R	20/80	35
1 1/4"	H-86155W	4/16	15

NEW PRESS DIELECTRIC UNION

- Helps prevent galvanic corrosion
- Compatible with popular press tools



DIELECTRIC UNION

Galvanized Steel & Forged DZR Brass w/ Nylon Insulator Ring

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372

SIZE	ITEM#	CTN/CASE	CASE WT
FIP × Press Union 250 PSI CWP Max/180°F Max			
1/2"	H-81102W	30/120	51
3/4"	H-81103W	30/120	75
1"	H-81104W	24/48	41

FORGED DZR BRASS UNION

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372 NSF/ANSI 14

SIZE	ITEM#	CTN/CASE	CASE WT
Press × F1960 PEX Union 250 PSI CWP Max/180°F Max			
1/2"	H-38102W	30/120	43
3/4"	H-38103W	30/120	64
1"	H-38104W	24/48	36
Press × F1807 PEX Union 250 PSI CWP Max/180°F Max			
1/2"	H-18102W	30/120	42
3/4"	H-18103W	30/120	60
1"	H-18104W	24/48	33

