

CAB Part Number	Safe Working Load of Hanger in Pounds*	Safe Working Load of Hanger in Kilograms*	Safe Working Load for Each Individual Carrier in Pounds*	Safe Working Load for Each Individual Carrier in Kilograms*	Typical Single Cable Spacing Interval in Feet	Typical Single Cable Spacing Interval in Meters	Qty/Box	Weight Per Box in Pounds	Weight Per Box in Kilograms
934	100	45			2 to 5	.6 - 1.5	100	12	5
936	210	95			2 to 5	.6 - 1.5	50	12	5
940	110	50			2 to 5	.6 - 1.5	50	15	7
950	50	23			2 to 5	.6 - 1.5	200	13	6
951	200	91			2 to 5	.6 - 1.5	100	13	6
952	175	80			2 to 5	.6 - 1.5	50	9	4
953	275	125			2 to 5	.6 - 1.5	50	16	7
954	275	125			2 to 5	.6 - 1.5	25	9	4
955	275	125			2 to 5	.6 - 1.5	25	10	5
956	240	109			2 to 5	.6 - 1.5	25	13	6
961	180	82			2 to 5	.6 - 1.5	50	13	6
965	90	41	60	27	2 to 5	.6 - 1.5	25	29	13
966	90	41	60	27	2 to 5	.6 - 1.5	10	16	7
988	112	51			2 to 5	.6 - 1.5	200	15	7
989	112	51			2 to 5	.6 - 1.5	100	9	4
990	112	51			2 to 5	.6 - 1.5	100	9	4
991	112	51			2 to 5	.6 - 1.5	100	11	5
3703	80	36			2 to 5	.6 - 1.5	200	17	8
3704	70	32			2 to 5	.6 - 1.5	50	13	6
3708	112	51			2 to 5	.6 - 1.5	200	13	6
3709	112	51			2 to 5	.6 - 1.5	200	14	6
3832	250	114			2 to 5	.6 - 1.5	200	24	11
4501	52	24			2 to 5	.6 - 1.5	25	20	9
4691	100	45	87	40	2 to 5	.6 - 1.5	10	40	18
4701	80	36	40	18	2 to 4	.6 - 1.3	50	10	5
4801	50	23			2 to 5	.6 - 1.5	100	11	5
4972	202	92			2 to 5	.6 - 1.5	200	20	9
5041	112	51			2 to 5	.6 - 1.5	100	7	3
5042	112	51			2 to 5	.6 - 1.5	100	7	3
5133	261	119	87	40	2 to 5	.6 - 1.5	10	32	15
5653	400	182	150	68	2 to 5	.6 - 1.5			0
5965	250	114			2 to 5	.6 - 1.5	100	22	10
6012	250	114			2 to 5	.6 - 1.5	200	24	11
6018	202	92			2 to 5	.6 - 1.5	200	19	9
6130	50	23			2 to 5	.6 - 1.5	100	9	4
6188	90	41	60	27	2 to 5	.6 - 1.5	25	44	20
6673	400	182			2 to 5	.6 - 1.5	100	32	15