



Steel Switch Boxes

1" DEEP - NON-GANGABLE - 6.5 CUBIC INCH CAPACITY

1¹⁵/₁₆" WIDE x 3³/₄" LONG



TP101



TP103

KNOCKOUTS

Cat. #	Bracket	Plastic Clamp	Conduit	Cable	Unit Qty.	Wt. Lbs. Per 100
TP101	"S"	No	1 - 1/2"	2	25	38
TP103	"S"	Yes	1 - 1/2"	2	25	39


1¹/₂" DEEP - NON-GANGABLE - 7.5 CUBIC INCH CAPACITY

2" WIDE x 3" LONG


UL LISTED




TP100



TP104



TP106




TP114

KNOCKOUTS

Cat. #	Bracket	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
FOR NONMETALLIC CABLE - CLAMPS IN EACH END							
TP100	—	Yes	2 - Cable	—	1 - 1/2"	50	43
TP104	"S", set 1/2"	—	2 - Cable	—	1 - 1/2"	50	50
FOR ARMORED & METAL CLAD (MCI) CABLE - CLAMPS IN EACH END							
TP106*	—	Yes	2 - Cable	—	1 - 1/2"	50	44
FOR CONDUIT - NO CLAMPS, FLUSH DEVICE							
TP114	—	Yes	1 - 1/2"	—	1 - 1/2"	50	39

*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.



Steel Switch Boxes

2" DEEP – GANGABLE – 10.0 CUBIC INCH CAPACITY


2" WIDE x 3" LONG

UL LISTED


CP




TP116




TP118



TP120



TP123




TP124




TP126



TP130



TP132



TP131
Hold-Tite

KNOCKOUTS

Cat. #	Bracket	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
FOR NONMETALLIC CABLE – CLAMPS IN EACH END							
TP116	—	Yes	2 – Cable	—	1 – 1/2"	50	53
TP118	"S", Set 5/8"	—	2 – Cable	—	1 – 1/2"	50	60
FOR ARMORED & METAL CLAD (MCI) CABLE – CLAMPS IN EACH END							
TP120*	—	Yes	2 – Cable	—	1 – 1/2"	50	54
TP123*	"F", Set 1/2"	—	2 – Cable	—	1 – 1/2"	50	63
TP124*	"S", Set 5/8"	—	2 – Cable	—	1 – 1/2"	50	61
FOR CONDUIT – NO CLAMPS, FLUSH DEVICE							
TP126	—	—	1 – 1/2"	2 – 1/2"	1 – 1/2"	50	47
TP130	—	Yes	1 – 1/2"	2 – 1/2"	1 – 1/2"	50	48
TP132	"S", Set 5/8"	—	1 – 1/2"	2 – 1/2", 1 Side	1 – 1/2"	50	58
TP131	Hold-Tite	Yes	1 – 1/2"-T	—	1 – 1/2"	50	52


*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™). MCAP™ is a registered trademark of Southwire Company.

Steel Switch Boxes


2 1/4" DEEP – GANGABLE – BEVELED CORNERS 10.5 CUBIC INCH CAPACITY

2" WIDE x 3" LONG

UL LISTED



TP134



TP137 Hold-Tite



TP138




KNOCKOUTS

Cat. #	Description	Ears	Bumps	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
CLAMP SCREWS THROUGH BEVELED CORNERS								
TP134	Gangable	—	Yes	2 – Cable	—	1 – 1/2"	50	51
TP137	Gangable	Yes	—	2 – Cable	—	1 – 1/2"	50	57
TP138	Gangable	Yes	—	2 – Cable	—	1 – 1/2"	50	55


2 1/2" DEEP – GANGABLE – 12.5 CUBIC INCH CAPACITY

2" WIDE x 3" LONG


UL LISTED




TP158




TP162




TP163




TP164
TP168




TP170




TP161



TP172



TP174



TP171

KNOCKOUTS

Cat. #	Bracket	Ears	Ground Pigtail	Leveling Bumps	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
FOR NONMETALLIC CABLE - CLAMPS IN EACH END									
TP158	—	—	—	Yes	2 – Cable, 1 – 1/2"	—	1 – 1/2"	50	59
TP115*	—	Yes	Yes	—	2 – Cable	1 – 1/2"	1 – 1/2"	50	63
TP161	Snap-In	Yes	—	—	2 – Cable	1 – 1/2"	—	50	73
TP162	—	Yes	—	—	2 – Cable	1 – 1/2"	1 – 1/2"	50	62
TP163	Hold-Tite	Yes	—	—	2 – Cable	—	1 – 1/2"	50	65
TP164	"F", Set 1/2"	—	—	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	71
TP168	"F", Set 1/4"	—	—	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	71
TP170	"S", Set 5/8"	—	—	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	69
TP172	"D", Set 5/8"	—	—	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	70
TP174	"D", Set 5/8"	—	Yes	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	71
TP171	"VP", Set 1/2"	—	—	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	73

*Not UL Listed


Steel Switch Boxes

2 1/2" DEEP – GANGABLE – 12.5 CUBIC INCH CAPACITY


2" WIDE x 3" LONG FOR ARMORED & METAL CLAD (MCI) CABLE – CLAMPS IN EACH END

UL LISTED


CP




TP177




TP178




TP179
Hold-Tite



TP180



TP184



TP185

KNOCKOUTS


Cat. #	Bracket	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP177*	Snap-In	Yes	2 – Cable	1 – 1/2"	—	50	74
TP178*	—	Yes	2 – Cable	1 – 1/2"	1 – 1/2"	50	63
TP179*	Hold-Tite	Yes	2 – Cable	—	1 – 1/2"	50	66
TP180*	"F", Set 1/2"	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	72
TP184*	"S", Set 5/8"	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	70
TP185*	"VP", Set 1/2"	—	2 – Cable, 1 – 1/2"	1 – 1/2"	1 – 1/2"	50	74

*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.


GANG BOXES SET BACK 1/2"

2 1/2" DEEP – 3 3/4" HIGH – 1/2" AND 3/4" CONCENTRIC KOs


UL LISTED




TP632



TP633



TP637



TP638

KNOCKOUTS


Cat. #	Gang	Bracket	Width	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100	Capacity Cu. In.
TP632	3	VP	5 9/16"	2	3	6	5	143	46.5
TP633	4	VP	7 3/8"	2	4	8	5	179	62.0
TP637	3	VS	5 9/16"	2	3	6	5	143	46.5
TP638	4	VS	7 3/8"	2	4	8	5	179	62.0

Crouse-Hinds
by **E.T.N**


Steel Switch Boxes

2 1/2" DEEP "EC" BOXES – GANGABLE – CUBIC INCH CAPACITY (SEE BELOW)


2" WIDE x 3" LONG
CLAMPS IN EACH END
UL LISTED



TP188



TP190



TP196


Note: The cubic capacity of any of our new work 2 1/2" Deep Switch Boxes can be increased to 18 cubic inches simply by adding our "EC" Extender to the sides of the box. This provides 5.5 extra cubic inches of space necessary to conform to revisions in the National Electrical Code. "EC" boxes are stocked factory assembled in popular styles; however, the "EC" Extender can be ordered separately for "Instant-On" assembly on the job with Eaton's Crouse-Hinds Switch Boxes.

KNOCKOUTS


Cat. #	Bracket	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100	Capacity Cu. In.
TP188	—	—	—	—	50	32	5.5
FOR NONMETALLIC CABLE							
TP190	"D", Set 5/8"	2 – Cable, 1 – 1/2"	—	1 – 1/2"	25	89	18.0
TP196	"S", Set 5/8"	2 – Cable, 1 – 1/2"	—	1 – 1/2"	25	89	18.0

2 1/2" DEEP – GANGABLE – 12.5 CUBIC INCH CAPACITY


2" WIDE x 3" LONG
FOR CONDUIT – NO CLAMPS
UL LISTED




TP214




TP216




TP217




TP218



TP220



TP222




TP224

KNOCKOUTS

Cat. #	Bracket	Ears	Leveling Bumps	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP214	—	—	Yes	1 – 1/2"	—	1 – 1/2"	50	55
TP216	Snap-In	Yes	—	1 – 1/2"	1 – 1/2"	—	50	69
TP217	—	Yes	—	1 – 1/2"	—	1 – 1/2"	50	64
TP218	—	Yes	—	1 – 1/2"	1 – 1/2"	1 – 1/2"	50	58
TP220	"F", Set 1/2"	—	—	1 – 1/2"	1 – 1/2", 1 Side	1 – 1/2"	50	66
TP222	"S", Set 5/8"	—	—	1 – 1/2"	1 – 1/2", 1 Side	1 – 1/2"	50	65
TP224	Hold-Tite	Yes	—	1 – 1/2"	—	1 – 1/2"	50	61

Crouse-Hinds

by E.T.N




Steel Switch Boxes

CP

2 1/2" DEEP SWITCH BOXES – "INSTANT ON" – 12.5 CUBIC INCH CAPACITY

2" WIDE x 3" LONG

WITH BUMPS – CLAMPS IN EACH END (BUMPS LEVEL THE BOX AGAINST THE SIDE OF STUD, TOP TO BOTTOM, FRONT TO BACK)




TP213

Cat. #	Clamps	Nails	KNOCKOUTS			Std. Unit Pkg.	Wt. Lbs. Per 100
			Each End	Each Side	Bottom		
TP213	Armored Cable	Angle	2 – Cable, 1 – 1/2"	–	1 – 1/2"	50	66


2 3/4" DEEP – GANGABLE – 14.0 CUBIC INCH CAPACITY

2" WIDE x 3" LONG


UL LISTED




TP660




TP662



TP664



TP668



TP670

Cat. #	Bracket	Ears	KNOCKOUTS			Unit Qty.	Wt. Lbs. Per 100
			Each End	Each Side	Bottom		
FOR NONMETALLIC CABLE – CLAMPS IN EACH END							
TP660	–	–	2 – Cable	1 – 1/2"	1 – 1/2"	50	62
TP662	–	Yes	2 – Cable	1 – 1/2"	1 – 1/2"	50	67
TP664	"S", Set 5/8"	–	2 – Cable	1 – 1/2"	1 – 1/2"	50	70
FOR ARMORED & METAL CLAD (MCI) CABLE – CLAMPS IN EACH END							
TP668*	–	Yes	2 – Cable	1 – 1/2"	1 – 1/2"	50	68
TP670*	"S", Set 5/8"	–	2 – Cable	1 – 1/2"	1 – 1/2"	50	71


*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.

Steel Switch Boxes

2³/₄" DEEP – GANGABLE – 14.0 CUBIC INCH CAPACITY

2" WIDE x 3" LONG
FOR CONDUIT – NO CLAMPS


UL LISTED




TP672
TP674



(TP676 – 1 screw ear)
(TP678 – 2 screw ears)



TP680
TP677




KNOCKOUTS

Cat. #	Bracket	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP672	—	—	1 – 1/2"	1 – 1/2"	1 – 1/2"	50	59
TP674	—	—	1 – 3/4"	1 – 3/4"	1 – 1/2"	50	59
TP676	—	Yes	1 – 1/2"	1 – 1/2"	1 – 1/2"	50	61
TP678	—	Yes	1 – 3/4"	1 – 3/4"	1 – 1/2"	50	61
TP680	"S", Set 5/8"	—	1 – 1/2"	1 – 1/2", 1 Side	1 – 1/2"	50	70
TP677	"S", Set 5/8"	—	1 – 3/4"	1 – 3/4", 1 Side	1 – 1/2"	50	70


3¹/₂" DEEP – GANGABLE – 18.0 CUBIC INCH CAPACITY

2" WIDE x 3" LONG
FOR NONMETALLIC CABLE – CLAMPS IN EACH END


UL LISTED




TP236




TP238




TP239



TP240



TP242



TP243

KNOCKOUTS

Cat. #	Bracket	Ground Pigtail	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP236	—	—	—	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	78
TP238	—	—	Yes	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	80
TP239	—	Yes	Yes	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	81
TP240	"F", Set 1/2"	—	—	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	88
TP242	"S", Set 7/8"	—	—	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	87
TP243	"S", Set 7/8"	Yes	—	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	88

Steel Switch Boxes


3 1/2" DEEP – GANGABLE – 18.0 CUBIC INCH CAPACITY

2" WIDE x 3" LONG


FOR ARMORED & METAL CLAD (MCI) CABLE – CLAMPS IN EACH END

UL LISTED


CP



TP244



TP249



TP246

KNOCKOUTS

Cat. #	Bracket	Ground Pigtail	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP244*	—	—	Yes	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	81
TP249*	—	Yes	Yes	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	82
TP246*	"S", Set 7/8"	—	—	2 – Cable, 1 – 1/2"	2 – 1/2"	1 – 1/2"	25	88


*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.

3 1/2" DEEP – GANGABLE – 18.0 CUBIC INCH CAPACITY


2" WIDE x 3" LONG

FOR CONDUIT – NO CLAMPS


UL LISTED



TP248
TP250



TP252



TP254

KNOCKOUTS

Cat. #	Bracket	Ears	Each End	Each Side	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP248	—	—	2 – 1/2"	2 – 1/2"	1 – 1/2"	25	74
TP250	—	—	2 – 3/4"	2 – 3/4"	1 – 1/2"	25	74
TP252	—	Yes	2 – 1/2"	2 – 1/2"	1 – 1/2"	25	76
TP254	—	Yes	2 – 3/4"	2 – 3/4"	1 – 1/2"	25	76