

Steel Square Boxes



4¹¹/₁₆" SQUARE OUTLET BOXES AND COVERS

Applications:

- For use with conduit
- For use in commercial and industrial applications, where larger sized conductor or wiring devices are needed and additional volume is required
- Can be ceiling mounted to be used as a junction box or to mount lighting fixtures
- Available in red for fire alarm applications

Features:

- Ideal for exposed work applications, providing an easy method for the installation of electrical devices (switches, receptacles, fans, lights, etc.)
- Raised ground screw location in the welded boxes saves time in installation
- Concentric knockouts have a 1/2" and 3/4" knockout in the same location for customer flexibility
- Knockouts are suitable for use without a bonding jumper in circuits above or below 250 volts
- Available in two depths for differing cubic capacity requirements
- Welded or drawn construction to match customer preference
- Extensive cover offering to meet various customer applications and needs



Certifications and Compliances:

- UL Listed

4¹¹/₁₆" SQUARE OUTLET BOXES – 29.5 CUBIC INCH CAPACITY

1¹/₂" DEEP WITH CONDUIT KOs

UL LISTED



TP523



TP548



TP549

Steel Boxes

Cat. #	Description	KNOCKOUTS		Unit Qty.	Wt. Lbs. Per 100
		Sides	Bottom		
29.5 CUBIC INCH CAPACITY					
TP523	Welded	12 – 1/2" & 3/4" C	2 – 1/2", 2 – 3/4"	25	99
TP523PF†	Welded	12 – 1/2" & 3/4" C	2 – 1/2", 2 – 3/4"	25	99
TP548	Drawn	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	84
TP548MSB	Drawn	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	95
TP549	Drawn	6 – 1/2", 6 – 1/2" & 3/4" C	3 – 1/2", 2 – 3/4"	25	84
TP549MSB	Drawn	6 – 1/2", 6 – 1/2" & 3/4" C	3 – 1/2", 2 – 3/4"	25	95

†TP catalog numbers ending in PF includes ground screw with pigtail lead


Steel Utility Boxes & Covers




UTILITY BOXES – CUBIC INCH CAPACITY (SEE BELOW)

4" LONG x 2 1/8" WIDE

UL LISTED




TP588, TP647



TP591



TP592, TP600,
TP602



TP598
TP605



TP594, TP596



TP604, TP606

Cat. #	Bracket	KNOCKOUTS		Unit Qty.	Wt. Lbs. Per 100
		Sides	Bottom		
1 1/4" DEEP – 8.5 CUBIC INCH CAPACITY					
TP647	—	8 – 1/2"	3 – 1/2"	50	40
1 1/2" DEEP – 10.3 CUBIC INCH CAPACITY					
TP588	—	8 – 1/2"	3 – 1/2"	50	42
TP591	"F", Set 1/4"	5 – 1/2"	3 – 1/2"	50	51
1 1/2" DEEP EXTENSION RINGS – 10.3 CUBIC INCH CAPACITY					
TP592	—	8 – 1/2"	—	50	36
1 7/8" DEEP – 13.0 CUBIC INCH CAPACITY					
TP594	—	8 – 1/2"	3 – 1/2"	50	50
TP596	—	6 – 3/4"	3 – 1/2"	50	50
TP598	"S", SET 1/2"	5 – 1/2"	3 – 1/2"	50	60
1 7/8" DEEP EXTENSION RINGS – 13.0 CUBIC INCH CAPACITY					
TP600	—	8 – 1/2"	—	50	41
TP602	—	6 – 3/4"	—	50	41
2 1/8" DEEP – 14.5 CUBIC INCH CAPACITY					
TP604	—	8 – 1/2"	3 – 1/2"	50	56
TP606	—	6 – 3/4"	3 – 1/2"	50	56
TP605	"S", Set 1/2"	5 – 1/2"	3 – 1/2"	50	66

UTILITY BOX COVERS


UL LISTED



TP608



TP610



TP612



TP613



TP614



TP616



TP618

Cat. #	Description	Unit Qty.	Wt. Lbs. Per 100
TP608*	Blank	100	10
TP610*	For 20 and 30 AMP, Twist Lock, 1 19/32" Diameter	100	9
TP612*	Single Receptacle, 1 13/32" Diameter	100	9
TP613*	For GFCI Device	100	7
TP614*	1/2" KO	100	10
TP616*	Duplex Receptacle	100	8
TP618*	One Toggle Switch	100	10

*CSA Certified

Steel Boxes