8733 Small Diameter

APOLLOPRESS® Press End Brass Union CxC (1/2" through 2")

SUBMITTAL SHEET

"Apollo" Flow Controls





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The **APOLLOPRESS® 8733 Small Diameter Press Union** features a lead free dezincification resistant brass body and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

FEATURES

- · Lead Free Construction
- Leak Before Press® Technology
- Ridgid® XL Press Tool Compatible
- · Made in USA

APPROVALS

- · UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- NSF/ANSI 61 Water Quality
- · NSF/ANSI 372 Lead Free
- IAPMO File Listings: 4861, 6174 & N-4951

PERFORMANCE RATING

- · Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

APOLLOPRESS®

- · Small Diameter Sizes 1/2" through 2"
- · Model 8733, Union


APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

STANDARD MATERIALS LIST

Body	UNS C27451 Brass					
0-Ring	EPDM					
Lubrication	Silicone, ANSI/NSF-61 Listed					

DIMENSIONS

ITEM NO.	SIZE (IN.)	DIMENSIONS (IN.)							WEIGHT	
HEM NO.		Α	В	С	D	E	HEIGHT	WIDTH	DEPTH	(LB.)
10075860	1/2	2.95	1.17	0.76	1.44	0.76	1.17	2.95	1.17	0.31
10075862	3/4	3.65	1.42	0.92	1.82	0.92	1.42	3.65	1.42	0.5
10075864	1	3.79	1.81	0.92	1.96	0.92	1.81	3.79	1.81	0.77
10075866	1-1/4	3.79	2.04	1.04	1.70	1.04	2.04	3.79	2.04	0.94
10075868	1-1/2	3.92	2.28	1.43	1.06	1.43	2.28	3.92	2.28	1.23
10075870	2	4.63	2.95	1.59	1.46	1.59	2.95	4.63	2.95	1.94



*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

