

• MALE THREADED X CPVC • LEAD FREE

Features

- Transition fitting for connection threaded pipe with CPVC pipe
- Durable over molded one-piece fitting eliminates potential leak path
- Lead Free Brass material
- Suitable for use in both residential and light commercial plumbing systems
- Molded CPVC end piece with slip connection



Specifications & Approvals

Pressure Rating: 100 PSI at 180°F
 Pressure Rating: 150 PSI at 100°F

- NSF/ANSI 61 (2012) Section 8
- NSF/ANSI 61 (2012) Annex F
- NSF/ANSI 61 (2012) Annex G
- NSF/ANSI 372
- Weighted Average Lead Content $\leq 0.25\%$
- Conforms to material and dimensional requirements of ASTM D-2846
- Threaded ends conform to ASME B 1.20.1
- Stocked in 1/2" - 2"



Dimensions

Part#	Size	H	E
BRCPM012-NL	1/2"	46	25
BRCPM034-NL	3/4"	53	30
BRCPM100-NL	1"	66	36
BRCPM114-NL	1-1/4"	78	43.4
BRCPM112-NL	1-1/2"	84	49.2
BRCPM200-NL	2"	99	61.1

Material Specifications

Part Name	Material
1. Fitting	C46400 Brass
2. CPVC	CPVC

