

Welded Sch 40 Specifications



- Black and hot-dipped galvanized steel pipe conforms to ASTM A53
- Welded steel nipples conform to ASTM A733
- NPT Threads on nipples conform to ASME B1.20
- Manufacturing facility is ISO 9001:2008 and ISO 14001
- Galvanized nipples are certified to; NSF/ANSI 372 and California AB1953 Lead Free

Black & Galvanized Sch 40

Size in	Close Length in	Close	1-1/2	2	2-1/2	3	3-1/2	4	4-1/2	5	5-1/2	6	7	8	9	10	11	12	
		Weight per Each (lb)																	
		Packing (Inner/Master)																	
1/8	3/4	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.10	0.12	0.15	0.16	0.18	0.21	0.23	0.25	
		25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/200	25/200	25/200	25/200
1/4	7/8	0.02	0.04	0.06	0.07	0.09	0.11	0.13	0.14	0.16	0.18	0.20	0.23	0.27	0.30	0.34	0.38	0.41	
		25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/400	25/300	25/300	25/300	25/200	25/200	25/200	20/160	20/160	20/160
3/8	1	0.03	0.06	0.09	0.11	0.14	0.16	0.19	0.22	0.24	0.27	0.30	0.35	0.40	0.46	0.51	0.56	0.62	
		25/400	25/400	25/400	25/400	25/400	25/300	25/300	25/200	25/200	25/200	25/200	25/150	25/150	25/100	25/100	25/100	25/100	25/100
1/2	1-1/8	0.05	0.08	0.12	0.15	0.19	0.22	0.26	0.29	0.33	0.36	0.40	0.47	0.54	0.61	0.68	0.75	0.83	
		25/400	25/400	25/400	25/300	25/300	25/200	25/200	25/200	25/150	25/150	25/150	25/100	25/100	25/100	25/75	25/75	25/75	25/75
3/4	1-3/8	0.08	0.10	0.15	0.20	0.24	0.29	0.34	0.39	0.43	0.48	0.53	0.62	0.72	0.81	0.91	1.00	1.09	
		25/400	25/400	25/300	25/300	25/200	25/200	25/150	25/150	25/100	25/100	25/100	25/75	25/75	25/50	25/50	25/50	25/50	25/50
1	1-1/2	0.14		0.16	0.23	0.30	0.37	0.44	0.51	0.58	0.65	0.72	0.86	1.00	1.14	1.28	1.42	1.56	
		25/200		25/200	25/150	25/150	25/100	25/100	25/100	25/75	25/75	25/50	25/50	25/50	25/50	25/50	20/40	20/40	20/40
1-1/4	1-5/8	0.21		0.27	0.36	0.45	0.55	0.64	0.74	0.83	0.93	1.02	1.21	1.40	1.59	1.78	1.97	2.16	
		25/150		25/100	25/100	25/100	25/50	25/50	25/50	25/50	25/50	25/50	15/30	15/30	15/30	-/30	-/30	-/30	-/30
1-1/2	1-3/4	0.26		0.32	0.43	0.55	0.66	0.77	0.89	1.00	1.11	1.23	1.45	1.68	1.91	2.13	2.36	2.59	
		25/100		25/100	25/50	25/50	25/50	25/50	20/40	20/40	20/40	-/35	-/35	-/35	-/15	-/15	-/15	-/15	-/15
2	2	0.46		0.61	0.76	0.91	1.07	1.22	1.37	1.52	1.68	1.98	2.28	2.59	2.89	3.20	3.50	3.50	
		25/50		25/50	-/50	-/25	-/25	-/25	-/25	-/25	-/25	-/18	-/18	-/18	-/18	-/14	-/14	-/14	-/14
2-1/2	2-1/2	0.75				0.95	1.19	1.43	1.67	1.91	2.16	2.40	2.88	3.36	3.85	4.33	4.81	5.30	
		-/36				-/36	-/27	-/27	-/24	-/18	-/18	-/18	-/14	-/12	-/12	-/9	-/9	-/9	-/9
3	2-5/8	0.99				1.19	1.50	1.82	2.14	2.45	2.77	3.08	3.72	4.35	4.98	5.61	6.24	6.88	
		-/24				-/24	-/18	-/18	-/16	-/12	-/12	-/12	-/9	-/8	-/8	-/6	-/6	-/6	-/6
3-1/2	2-3/4	2.08						3.03	3.41	3.79	4.17	4.55	5.31	6.10	6.83	7.59	8.34	9.11	
		-/15						-/12	-/10	-/8	-/8	-/8	-/5	-/5	-/5	-/4	-/4	-/4	-/4
4	2-7/8	1.74						3.59	4.04	4.49	4.94	5.39	6.29	7.19	8.09	8.99	9.89	10.79	
		-/15						-/12	-/10	-/8	-/8	-/8	-/5	-/5	-/4	-/4	-/4	-/4	-/4
5	3	4.26						3.83	4.31	5.05	5.72	6.27	6.27	8.70	10.96	11.14	12.25	13.58	
		-/4						-/4	-/4	-/2	-/2	-/2	-/2	-/2	-/2	-/2	-/1	-/1	-/1
6	3-1/8	3.19						4.17	5.06	5.94	6.83	7.72	11.06	11.27	13.04	14.82	16.59	18.37	
		-/4						-/4	-/4	-/2	-/2	-/2	-/2	-/2	-/2	-/2	-/1	-/1	-/1