



## ENGINEERING & TECHNICAL DATA — Flexadux PU<sup>®</sup> Flex-Thane<sup>®</sup> MD

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.25	.030	2	3:1	29	30
2.5	.32	.030	2.5	3:1	29	30
3	.4	.030	3	3:1	29	29
3.5	.52	.030	3.5	3:1	22	28
4	.7	.030	4	3:1	29	25
5	.9	.030	5	3:1	17	22
6	1	.030	6	3:1	15	19
7	1.2	.030	7	3:1	12	16
8	1.5	.030	8	3:1	9	14
9	1.55	.030	9	3:1	5	12
10	1.6	.030	8	3:1	4	11
12	2	.030	10	3:1	2.2	10
14	2.5	.030	12	3:1	3.3	8
16	3	.030	14	3:1	2.2	7
18	3.3	.030	16	3:1	1.4	6
20	3.7	.030	18	3:1	1	5.5
22	4.1	.030	20	3:1	.9	5
24	4.5	.030	22	3:1	.75	4

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Medium weight polyurethane hose reinforced with a bronze coated spring steel wire helix

**Temperature Range:** -65°F to 225°F

**Standard Color:** Black and Clear

**Standard Lengths:** 25 & 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

**Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464**  
**sales@flexaust.com • www.flexaust.com**

