

PLYTUFF® - F/R PVC Jacketing Tape

PVC tape specifically formulated for flame resistance and abrasion resistance. Use for repairing nicks and tears in all mining cables. Use this tape for primary insulation through 600V. Ideally suited for securing premolded and shrinkable sleeve ends to the cable jacket. Title 30-CFR 18.64, P-153-MSHA Acceptance.

GLF® Jacket Repair Wrap

Use as a jacket repair or Vconditions tear or puncture the original cable jacket or conduit. Extremely abrasion-resistant, with excellent moisture exclusion properties. Approved under 30 CFR 7.404, approval number P-7K-SK-153082-1-MSHA.

GLF2® NEW Jacket Repair Wrap

Is our newest laminate of a specially formulated Hypalon backing and 2 flame-retardant mastic layers possessing the superior abrasion and moisture resistance required for all types of cable jacket repair. The laminate is easy to apply and remains flexible at low temperatures. GLF 2 will adhere to all types of cable jackets yielding a positive moisture seal. GLF 2 with approval number P-7K-SK-153082-1-MSHA.



PLYTUFF® - F/R PVC Jacketing Tapes

Cat.	Dimensions	Packaging	Weight
3880	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100/case C 23 lbs 10 kg
3881	1 1/2" x .007" x 66'	38mm x 0,18mm x 20m	100/case C 43 lbs 20 kg
3897	1 1/2" x .007" x 44'	38mm x ,018mm x 13m	100/case C 31 lbs 14 kg

GLF® Jacket Repair Wrap

Cat.	Dimensions	Packaging	Weight
2563	2" x .075" x 6'	51mm x 1,3mm x 1,8m	30/case C 16 lbs 7 kg
2564	2" x .075" x 8.5'	51mm x 1,3mm x 2,6m	20/case C 16 lbs 6 kg



GLF2® Jacket Repair Wrap (With extra layer of adhesive)

Cat.	Dimensions	Packaging	Weight
2501	2 in x 7 ft.	51mm x 2,15 m	30 / Case C 30 lbs 11 kg
2502	2 in x 9,5 ft.	51mm x 2,90 m	30 / Case C 30 lbs 14 kg