801 Small Diameter

APOLLOPRESS® Press End Copper Coupling without Stop CxC (1/2" through 2")

SUBMITTAL SHEET

"Apollo" Flow Controls





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The APOLLOPRESS® 801 Small Diameter Press Coupling features a lead free dezincification resistant copper body and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

FEATURES

- · Lead Free Construction
- Ridgid® XL Press Tool Compatible
- Leak Before Press® Technology
- Made in USA

APPROVALS

- UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- · NSF/ANSI 61 Water Quality
- · NSF/ANSI 372 Lead Free

PERFORMANCE RATING

- · Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

APOLLOPRESS®

- Small Diameter Sizes 1/2", 3/4", 1", 1-1/4" 1-1/2"
 & 2"
- · Model 801, Coupling without Stop


APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

STANDARD MATERIALS LIST

Body	UNS C12200 Copper				
0-Ring	EPDM				
Lubrication	Silicone, ANSI/NSF-61 Listed				

DIMENSIONS

ITEM NO.	SIZE (IN.)		WEIGHTAIRS				
HEM NO.		A	В	HEIGHT	WIDTH	DEPTH	WEIGHT (LB.)
10075513	1/2	1.72	0.95	0.95	1.72	0.95	0.08
10075515	3/4	1.89	1.24	1.24	1.89	1.24	0.13
10075517	1	2.07	1.49	1.49	2.07	1.49	0.19
10075521	1-1/4	2.33	1.75	1.75	2.33	1.75	0.25
10075523	1-1/2	3.1	2.11	2.11	3.1	2.11	0.5
10075527	2	3.31	2.58	2.58	3.31	2.58	0.62



*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

