



Features

- Die-cast, UV resistant powder coated aluminum housing with tempered glass lens and molded gasket with silicone seal
- 1/2" NPS plugs compatible with dusk to dawn photocell accessory
- Adjustable swivel arm can be extended with optional 4" extensions for additional clearance
- cULus Listed, IP65 (wet location)
- 50,000 hours rated life

Available Finishes



White



Dark Bronze

Listing / Ratings



Panorama Sunset Series

Updated for 2019, the new Panorama Sunset Series offers an admirable increase in lumen output while maintaining its low wattage energy consumption. Built from durable UV resistant materials which ensure maintenance-free operation over its long 50,000 hour rated life.

Technical Information

Series	ALV3
Input Voltage	120V AC
CCT	3000K
CRI	80+
Wattage	12W / 24W / 48W
Lumens	1000 - 4000Lm
Beam Angle	See individual product
Dimmable	N/A
Dimensions	See individual product
Mounting	Surface mount
Rating	cULus Listed (wet location)
Rated Life	50,000 hrs

Panorama Sunset Series

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

DECORATIVE LAMPS

PANORAMA SUNSET
ARCHITECTURAL LIGHTING

POWER SUPPLIES



Panorama Sunset 48

ALV3-48WF-WH (White)

ALV3-48WF-DB (Dark Bronze)

(3000K / 48W / 4000Lm / 80+ CRI)

60° x 120° Beam Angle / 183° Tilt

4.43"Dia. (Base) x 8"W x 6.69"H Face



Panorama Sunset 24

ALV3-WF-WH (White)

ALV3-WF-DB (Dark Bronze)

(3000K / 24W / 2000Lm / 80+ CRI)

60° x 120° Beam Angle / 183° Tilt

4.43"Dia. (Base) x 3.75"W x 5.25"H Face



Panorama Sunset Double

ALV3-2H-WH (White)

ALV3-2H-DB (Dark Bronze)

(3000K / 24W / 2000Lm / 80+ CRI)

2 x 95° Beam Angle / 2 x 105° Tilt

4.43"Dia. (Base) 5"H



Panorama Sunset Single

ALV3-1H-WH (White)

ALV3-1H-DB (Dark Bronze)

(3000K / 12W / 1000Lm / 80+ CRI)

95° Beam Angle / 180° Tilt

4.43"Dia. (Base) 4.75"H