

Rigid Watertight Hubs

With Bonding Screw - Zinc Die Cast

Features

- Flame-retardant insulated throat
- Rain, oil, and dust tight
- Oversized locknut protects against damage from vibrations and promotes positive grounding

Applications

- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes


Standard Material

- Zinc die cast



E195122

NEMA 2 3R, 4, 4X, 5, 12, 13



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches		Max. Copper Wire Size UL#
						A	B	
201B	11551	1/2"	25	250	53	1.31	1.54	#8
202B	11561	3/4"	10	100	30	1.37	1.73	#8
203B	11571	1"	10	100	43	1.59	2.04	#8
204B	11581	1-1/4"	2	20	12	1.59	2.42	#8
205B	11591	1-1/2"	2	20	15	1.59	2.79	#8
206B	11601	2"	2	20	10	1.59	3.30	#8
207B	11611	2-1/2"	---	2	8	2.44	3.70	#6
208B	11621	3"	---	2	10	2.44	4.39	#6
209B	11631	3-1/2"	---	1	13	2.44	4.88	#6
210B	11641	4"	---	1	15	2.44	5.50	#4