



COMPATIBLE WITH MOST JUNCTION BOXES AND 4" HOUSINGS

ENGINEERED FOR VERSATILITY AND PERFORMANCE

The Elite RL470 has been engineered for New Construction, Remodel and Retrofit applications for 4 inch downlights as well as applications in standard junction boxes. Dedicated housings install the same way as our standard incandescent downlights and include features such as adjustable, lockable and tilting bar hangers. Over 650 usable lumens are directed from the luminaire to the work surface. Lighting is smooth and comfortable, all while using 75% less energy than the equivalent 50W BR20 and 25% less than the common 13W CFL. Plus the Elite RL470 features 50,000 hours of life, and California Title-24 compliance.


INPUT VOLT.	INPUT FREQ.	THD	POWER FACTOR	INPUT POWER	LUMENS
120	60Hz	<20%	>0.95	10W(+/-5%)	650

FEATURES

Greater light output than an 13W CFL or a 50W BR20 while consuming only 10W of power. Fits in most 4 inch downlight housings and junction boxes.

OPTICS

The Elite-Engineered LED Module system is much more than just a simple LED retrofit. The Elite LED system is a highly engineered work of design and optical science which produces over 650 lumens! Our meticulously crafted optics gather the light scattered by the LED chip and shape it into a functional beam with uniform light distribution.



DURABILITY

Die-cast aluminum housing and heat management system are engineered for extremely long life and service period. Without proper heat management, any LED luminaire will fail. Our die-cast system pulls the heat from the LED chip, allowing the continued cool operation for years. Life tests have shown the Elite RL470 light output will be maintained at 70% of initial at 50,000 hours of operation. Our superior design allows for installation in construction that requires the Elite Air-Shut™ system. Our LED driver is rated for 50 to 60 Htz at 120V input, produces less than 20% THD, has a power factor between 0.90 and 1.00 and is thermal protected for additional safety. For installations requiring a 277V driver please consult the factory.

REPEATABLE

Repeatability means quality. From our chip selection process, to our driver, to the thermal management, the Elite RL470 Module is engineered for quality. All Elite LED luminaires are rated at 85+ or 90+ CRI, as rated and tested to LM-79 and LM-80 standards by a certified laboratory, and meets the California Title-24 compliance standards. Elite's highly selective LED chips produce zero ultraviolet and virtually no infrared light.

DIMMABLE

The Elite RL470 lighting system is dimmable down to 10% by using an approved dimmer. Refer to dimming matrix for more information.

INTERCHANGEABLE

The Elite RL470 LED system fits in most junction boxes, our dedicated (LD4IC-AT, LD4RIC-AT) housings and our existing 4" Incandescent housings.

ADAPTABLE

All Elite RL470 luminaires are shipped standard with our custom engineered Edison adapter. This adapter assembly allows the luminaires to install directly into existing Elite 4" incandescent downlight housings and most other 4" incandescent downlight housings. GU24 style socket base adapters also available upon request.

OUR WORD

The Elite LED lighting system carries a five-year carefree warranty for parts and components. (Labor not included)

INSTALLATION

- Comes with industry standard torsion springs or mounting clips that can be adjusted to fit in most junction boxes and most 4" downlight housings. Custom designed bracket included for mounting in standard size junction box.



CERTIFICATIONS

- cULus
- RoHS
- IECC
- New York state
- UL/cUL Listed for Damp Location
- California Title 24
- Washington state
- LM79/LM80

RL470

UNIVERSAL 4" SURFACE MOUNT LED MODULE

Example: **RL470-650L-DIMTR-120-30K-90-W-WH**

TYPE	650L SERIES	CCT	CRI	FINISH	RING TRIM	OPTION
RL470	<input type="checkbox"/> 650L-DIMTR-120	<input type="checkbox"/> 27K <input type="checkbox"/> 30K <input type="checkbox"/> 40K	<input type="checkbox"/> 90+	<input type="checkbox"/> W-WH	<input type="checkbox"/> RL470-RT-BK <input type="checkbox"/> RL470-RT-BZ <input type="checkbox"/> RL470-RT-SN	<input type="checkbox"/> GU24SA GU24 SOCKET ADAPTER

AVAILABLE COLOR INSERTS FOR RL470 - 4" RETROFIT

RING TRIM



RL470-RT-BK



RL470-RT-BZ



RL470-RT-SN

Ordering Guide for Compatible Housing

IC - New Construction	Non-IC New Construction	IC - For Remodel	Non-IC For Remodel
LD4IC-AT	LD4-AT	LD4RIC-AT	LD4R-AT
HLD4IC-AT	HLD4-AT		HLD4R-AT
B4IC-AT	B4-AT		B4R-AT

*RECOMMENDED DIMMERS FOR ELITE RL470 LED SYSTEM

LUTRON DIMMERS

DIMTR

Diva DVCL-153P
Skylark CTCL-153P
Nova N-600
NovaT NT-600
Skylark S-600
Ariadni AY-600P
Nova NTLV-600
Nova NLV-600

Maestro MRF2-6ND
NovaT NTELV-600
Diva DVELV-300P
Skylark SELV-300P
Nova NELV-450




3 3/4" Round
(Plastic)



3 3/4" Square
(Plastic)



3 3/4" Octagonal
(Metal)



4" Square
(Metal)
with Mud Ring



Fire Rated J-Box

Note: A 2-1/8" deep octagon junction box is recommended for through circuit wiring applications.

