

LED OPAL SERIES

Surface or Recessed Mount

The Opal Series LED fixture is designed to surface mount over a standard junction box or is suitable for use with a recessed housing by Nora or others. The Opal produces even illumination with no diode image, from bright to dim. The low profile unit is cULus wet listed and produces 650 to 2000 lumens at 90+ CRI. Available in three finishes the Opal is an excellent energy efficient lighting solution for laundry rooms, closets, pantries, hallways and showers in residential and commercial retrofit or new construction applications.

FEATURES

- 4" - 650 lumens / 10.5W or T24 850 lumens / 13W
- 6" - 1050 lumens / 16W
- 8" - 2000 lumens / 32W
- 2700K, 3000K, 4000K or 5000K at 90+ CRI
- No driver required, wires directly to AC input
- Nora designed, precision molded lens provides optimal lumen output and even distribution
- White polymer lens diffuser eliminates diode image, even when dimmed
- Medium base socket for easy retrofitting in a 5" or 6" recessed housing
- Fits most 4" junction boxes
- White, Natural Metal and Bronze finishes
- Dimmable down to 5%
- Suitable for use in closets, compliant with NFPA[®] 70, NEC[®] Section 410.16 (A)(3) and 410.16 (C)(5)
- T24 series can be used to comply with 2016 Title 24 Part 6 High Efficacy LED light source requirements
- 5-Year limited warranty
- ENERGY STAR[®] certified



4" & 6" AC OPAL SERIES



4", 6" & 8" AC T24 OPAL SERIES



LED AC OPAL SERIES 4", 6" & 8" SURFACE MOUNT

| SIZE / LUMENS / WATTAGE | COLOR TEMP | FINISH |
|--|--|--|
| NLOPAC-R4509 = 4" / 650lm / 10.5W | 27A = 2700K | BZ = Bronze N = Natural Metal W = White |
| NLOPAC-R6509 = 6" / 1050lm / 16W | 30A = 3000K | |
| | 40A = 4000K | |
| | 50A = 5000K (White finish only) | |
| NLOPAC-R4T24 = 4" / 850lm / 13W | 27 = 2700K | |
| NLOPAC-R6T24 = 6" / 1050lm / 16W | 30 = 3000K | |
| NLOPAC-R8T24 = 8" / 2000lm / 32W | 40 = 4000K | |



Example: **NLOPAC-R4T2430W** - 4" T24 AC Opal LED, 850lm / 13W, 3000K, White finish.

OPTIONAL ACCESSORIES

- NLOPAC-56RECKIT** 6" Opal can be mounted on 5" or 6" recessed housing using optional torsion spring kit.
- NLOPAC-4BKT-2** Universal bracket for mounting 4" and 6" Opal to 3" or 4" junction boxes. Universal bracket is included with R4509 series.

