




Seamless connections for the perfect glare-free solution for reflective task surfaces
 Luxurious color rendering for full color spectrum illumination
 High/Low switch for optimal lighting control
 Detachable design for ease of installation and maintenance

LINE™

LED Edge Lit Task Luminaires

Rated Life: 80,000 hours
Color Temp: 3000K
CRI: 85
Dimming: 100% – 10%



Professional, asymmetrical forward throw illumination for full coverage of the task plane

Order Number


Model	Length	Finish
LN-LED06-30-AL	6"	Brushed Aluminum
LN-LED12-30-AL	12"	
LN-LED18-30-AL	18"	
LN-LED24-30-AL	24"	
LN-LED30-30-AL	30"	

Performance

Power	Lumens
7 W	280
12.5 W	600
19 W	955
23 W	1245
26 W	1345

Max Fixture Run

60 W Trans	96 W Trans
8	13
4	7
3	5
2	4
2	3



120V Class 2 Electronic Transformers

Type	Model	Dim	Input	Output
Remote	EN-2460-RB2-S	Yes	120V	24V AC/60W
	EN-24100-RB2-S			24V AC/96W
Plug-In	EN-2460-P-AR-S	Yes	120V	24V AC/60W
	EN-24100-P-AR-S			24V AC/96W

Includes 6' cord and 5 SL-WC-1 clips.

277V Class 2 Electronic Transformer

Remote	EN-24100-277-R	No	277V	24V DC/100W
--------	-----------------------	----	------	-------------

Includes 1' input and output wires.

Connection Accessories

SL-I	"I" Connector	SL-IC-06	6" Joiner Cable
SL-IF	Joiner Cable Extender	SL-IC-12	12" Joiner Cable
SL-X	X Connector	SL-IC-24	24" Joiner Cable
SL-Y	Y Connector	SL-IC-36	36" Joiner Cable

Power Supply Accessories

TB-S	Wiring box	Use when spanning a large gap in a system layout without exposed wiring.
MTB-06	6 output terminal block	Neatly wire multiple output connections.
MTB-08	8 output terminal block	
SL-EXT-144	12' extension cable	Extends distance between a power supply or wiring box to a LINE section.
SL-WC-1	Wire Clip	Use to neatly tack down cords and cables.