

**Common Name:** INDUSTRIAL WORK DAY ENAMEL SPRAY PAINT, ORANGE

**Manufacturer:** KRYLON PRODUCTS GROUP

**SDS Revision Date:** 11/23/2022

**SDS Format:** No Format Specified

**Item Number(s):** 800T21

**Manufacturer Model  
Number(s):**

### SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

---

[SECTION 1. IDENTIFICATION](#)  
[SECTION 2. HAZARDS IDENTIFICATION](#)  
[SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS](#)  
[SECTION 4. FIRST AID MEASURES](#)  
[SECTION 5. FIRE-FIGHTING MEASURES](#)  
[SECTION 6. ACCIDENTAL RELEASE MEASURES](#)  
[SECTION 7. HANDLING AND STORAGE](#)  
[SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)  
[SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES](#)  
[SECTION 10. STABILITY AND REACTIVITY](#)  
[SECTION 11. TOXICOLOGICAL INFORMATION](#)  
[SECTION 12. ECOLOGICAL INFORMATION](#)  
[SECTION 13. DISPOSAL CONSIDERATIONS](#)  
[SECTION 14. TRANSPORT INFORMATION](#)  
[SECTION 15. REGULATORY INFORMATION](#)  
[SECTION 16. OTHER INFORMATION](#)

---

SAFETY DATA SHEET

A04413007

### SECTION 1. IDENTIFICATION

PRODUCT NAME: INDUSTRIAL WORK DAY(TM) ENAMEL SPRAY PAINT ORANGE

PRODUCT CODE: A04413007

OTHER MEANS OF IDENTIFICATION: NOT AVAILABLE.

PRODUCT TYPE: AEROSOL.

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: PAINT OR PAINT RELATED MATERIAL.

MANUFACTURER:  
KRYLON PRODUCTS GROUP  
101 PROSPECT AVENUE NW  
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NUMBER OF THE COMPANY:  
US/CANADA: (800) 424-9300

MEXICO:  
CHEMTREC MEXICO 800-681-9531. AVAILABLE 24 HOURS AND 365 DAYS PER YEAR

PRODUCT INFORMATION TELEPHONE NUMBER:  
US/CANADA: (800) 247-3266  
MEXICO: NOT AVAILABLE

REGULATORY INFORMATION TELEPHONE NUMBER:  
US/CANADA: (216) 566-2902  
MEXICO: NOT AVAILABLE

TRANSPORTATION EMERGENCY TELEPHONE NUMBER:  
US/CANADA: (800) 424-9300

MEXICO:  
SETIQ 800-00-214-00 / 55-5559-1588 AVAILABLE 24 HOURS AND 365 DAYS A YEAR

## **SECTION 2. HAZARDS IDENTIFICATION**

OSHA/HCS STATUS:  
THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:  
FLAMMABLE AEROSOLS: CATEGORY 1

GASES UNDER PRESSURE: COMPRESSED GAS

SKIN CORROSION/IRRITATION: CATEGORY 2

SERIOUS EYE DAMAGE/EYE IRRITATION: CATEGORY 2A

SKIN SENSITIZATION: CATEGORY 1

CARCINOGENICITY: CATEGORY 2

TOXIC TO REPRODUCTION: CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)  
(RESPIRATORY TRACT IRRITATION): CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (NARCOTIC EFFECTS):  
CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): CATEGORY 2

ASPIRATION HAZARD: CATEGORY 1

PERCENTAGE OF THE MIXTURE CONSISTING OF INGREDIENT(S) OF UNKNOWN ACUTE TOXICITY: 15.3% (ORAL), 27.8% (DERMAL), 24.3% (INHALATION)

GHS LABEL ELEMENTS:

HAZARD PICTOGRAMS:

FLAME

GAS CYLINDER

HEALTH HAZARD

EXCLAMATION MARK

SIGNAL WORD: DANGER

HAZARD STATEMENTS:

EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE RESPIRATORY IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

SUSPECTED OF CAUSING CANCER.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENTS:

PREVENTION:

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. WEAR PROTECTIVE GLOVES, PROTECTIVE CLOTHING AND EYE OR FACE PROTECTION. KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. NO SMOKING. DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE. USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. DO NOT BREATHE DUST OR MIST. WASH THOROUGHLY AFTER HANDLING. CONTAMINATED WORK CLOTHING MUST NOT BE ALLOWED OUT OF THE WORKPLACE.

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

RESPONSE:

IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE OR ATTENTION.

IF INHALED:

REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR DOCTOR IF YOU FEEL UNWELL.

IF SWALLOWED:

IMMEDIATELY CALL A POISON CENTER OR DOCTOR. DO NOT INDUCE VOMITING. TAKE OFF CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE. WASH CONTAMINATED CLOTHING BEFORE REUSE.

IF ON SKIN: WASH WITH PLENTY OF WATER.

IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE OR ATTENTION.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE OR ATTENTION.

STORAGE:

STORE LOCKED UP. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F. STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

DISPOSAL:

DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH ALL LOCAL, REGIONAL, NATIONAL AND INTERNATIONAL REGULATIONS.

SUPPLEMENTAL LABEL ELEMENTS:

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. CONTAINS SOLVENTS WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

WARNING:

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. FOR INDUSTRIAL USE ONLY.

PLEASE REFER TO THE SDS FOR ADDITIONAL INFORMATION. KEEP OUT OF REACH OF CHILDREN. KEEP UPRIGHT IN A COOL, DRY PLACE. DO NOT DISCARD EMPTY CAN IN TRASH COMPACTOR.

HAZARDS NOT OTHERWISE CLASSIFIED:

DANGER:

RAGS, STEEL WOOL, OTHER WASTE SOAKED WITH THIS PRODUCT, AND SANDING RESIDUE MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY PLACE RAGS, STEEL WOOL, OTHER WASTE SOAKED WITH THIS PRODUCT, AND SANDING RESIDUE IN A SEALED, WATER-FILLED, METAL CONTAINER. DISPOSE OF IN ACCORDANCE WITH LOCAL FIRE REGULATIONS.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE: MIXTURE

OTHER MEANS OF IDENTIFICATION: NOT AVAILABLE.

CAS NUMBER/OTHER IDENTIFIERS:

INGREDIENT NAME	% BY WEIGHT	CAS NUMBER
ACETONE	>/=25 - </=50	67-64-1

PROPANE	>/=10 - </=25	74-98-6
BUTANE	>/=10 - </=25	106-97-8
TOLUENE	</=10	108-88-3
ISOBUTYL ACETATE	</=10	110-19-0
ETHYL 3-ETHOXYPROPIONATE	</=3.2	763-69-9
TRIMETHYLPENTANEDIOL DIISOBUTYRATE	</=1	6846-50-0
TITANIUM DIOXIDE	</=1	13463-67-7
METHYL ETHYL KETOXIME	</=0.3	96-29-7

ANY CONCENTRATION SHOWN AS A RANGE IS TO PROTECT CONFIDENTIALITY OR IS DUE TO BATCH VARIATION.

THERE ARE NO ADDITIONAL INGREDIENTS PRESENT WHICH, WITHIN THE CURRENT KNOWLEDGE OF THE SUPPLIER AND IN THE CONCENTRATIONS APPLICABLE, ARE CLASSIFIED AND HENCE REQUIRE REPORTING IN THIS SECTION.

OCCUPATIONAL EXPOSURE LIMITS, IF AVAILABLE, ARE LISTED IN SECTION 8.

## SECTION 4. FIRST AID MEASURES

### DESCRIPTION OF NECESSARY FIRST AID MEASURES:

#### EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, OCCASIONALLY LIFTING THE UPPER AND LOWER EYELIDS. CHECK FOR AND REMOVE ANY CONTACT LENSES. CONTINUE TO RINSE FOR AT LEAST 10 MINUTES. GET MEDICAL ATTENTION.

#### INHALATION:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. IF IT IS SUSPECTED THAT FUMES ARE STILL PRESENT, THE RESCUER SHOULD WEAR AN APPROPRIATE MASK OR SELF-CONTAINED BREATHING APPARATUS. IF NOT BREATHING, IF BREATHING IS IRREGULAR OR IF RESPIRATORY ARREST OCCURS, PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN BY TRAINED PERSONNEL. IT MAY BE DANGEROUS TO THE PERSON PROVIDING AID TO GIVE MOUTH-TO-MOUTH RESUSCITATION. GET MEDICAL ATTENTION. IF NECESSARY, CALL A POISON CENTER OR PHYSICIAN. IF UNCONSCIOUS, PLACE IN RECOVERY POSITION AND GET MEDICAL ATTENTION IMMEDIATELY. MAINTAIN AN OPEN AIRWAY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

#### SKIN CONTACT:

WASH WITH PLENTY OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CONTAMINATED CLOTHING THOROUGHLY WITH WATER BEFORE REMOVING IT, OR WEAR GLOVES. CONTINUE TO RINSE FOR AT LEAST 10 MINUTES. GET MEDICAL ATTENTION. IN THE EVENT OF ANY COMPLAINTS OR SYMPTOMS, AVOID FURTHER EXPOSURE. WASH CLOTHING BEFORE REUSE. CLEAN SHOES THOROUGHLY BEFORE REUSE.

INGESTION:

GET MEDICAL ATTENTION IMMEDIATELY. CALL A POISON CENTER OR PHYSICIAN. WASH OUT MOUTH WITH WATER. REMOVE DENTURES IF ANY. IF MATERIAL HAS BEEN SWALLOWED AND THE EXPOSED PERSON IS CONSCIOUS, GIVE SMALL QUANTITIES OF WATER TO DRINK. STOP IF THE EXPOSED PERSON FEELS SICK AS VOMITING MAY BE DANGEROUS. ASPIRATION HAZARD IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE. DO NOT INDUCE VOMITING. IF VOMITING OCCURS, THE HEAD SHOULD BE KEPT LOW SO THAT VOMIT DOES NOT ENTER THE LUNGS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF UNCONSCIOUS, PLACE IN RECOVERY POSITION AND GET MEDICAL ATTENTION IMMEDIATELY. MAINTAIN AN OPEN AIRWAY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

POTENTIAL ACUTE HEALTH EFFECTS:

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION.

INHALATION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE RESPIRATORY IRRITATION.

SKIN CONTACT: CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.

INGESTION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

OVER-EXPOSURE SIGNS/SYMPTOMS:

EYE CONTACT:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

PAIN OR IRRITATION  
WATERING  
REDNESS

INHALATION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

RESPIRATORY TRACT IRRITATION  
COUGHING  
NAUSEA OR VOMITING  
HEADACHE  
DROWSINESS/FATIGUE  
DIZZINESS/VERTIGO  
UNCONSCIOUSNESS  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

SKIN CONTACT:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

IRRITATION  
REDNESS  
REDUCED FETAL WEIGHT

INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

INGESTION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

NAUSEA OR VOMITING  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED,  
IF NECESSARY:

NOTES TO PHYSICIAN:

TREAT SYMPTOMATICALLY. CONTACT POISON TREATMENT SPECIALIST IMMEDIATELY IF  
LARGE QUANTITIES HAVE BEEN INGESTED OR INHALED.

SPECIFIC TREATMENTS: NO SPECIFIC TREATMENT.

PROTECTION OF FIRST-AIDERS:

NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE  
TRAINING. IF IT IS SUSPECTED THAT FUMES ARE STILL PRESENT, THE RESCUER  
SHOULD WEAR AN APPROPRIATE MASK OR SELF-CONTAINED BREATHING APPARATUS. IT  
MAY BE DANGEROUS TO THE PERSON PROVIDING AID TO GIVE MOUTH-TO-MOUTH  
RESUSCITATION. WASH CONTAMINATED CLOTHING THOROUGHLY WITH WATER BEFORE  
REMOVING IT, OR WEAR GLOVES.

SEE TOXICOLOGICAL INFORMATION (SECTION 11)

## **SECTION 5. FIRE-FIGHTING MEASURES**

EXTINGUISHING MEDIA:

SUITABLE EXTINGUISHING MEDIA:

USE AN EXTINGUISHING AGENT SUITABLE FOR THE SURROUNDING FIRE.

UNSUITABLE EXTINGUISHING MEDIA: NONE KNOWN.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

EXTREMELY FLAMMABLE AEROSOL. RUNOFF TO SEWER MAY CREATE FIRE OR EXPLOSION  
HAZARD. IN A FIRE OR IF HEATED, A PRESSURE INCREASE WILL OCCUR AND THE  
CONTAINER MAY BURST, WITH THE RISK OF A SUBSEQUENT EXPLOSION. GAS MAY  
ACCUMULATE IN LOW OR CONFINED AREAS OR TRAVEL A CONSIDERABLE DISTANCE TO  
A SOURCE OF IGNITION AND FLASH BACK, CAUSING FIRE OR EXPLOSION. BURSTING  
AEROSOL CONTAINERS MAY BE PROPELLED FROM A FIRE AT HIGH SPEED.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

DECOMPOSITION PRODUCTS MAY INCLUDE THE FOLLOWING MATERIALS:

CARBON DIOXIDE  
CARBON MONOXIDE

SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS:

PROMPTLY ISOLATE THE SCENE BY REMOVING ALL PERSONS FROM THE VICINITY OF THE INCIDENT IF THERE IS A FIRE. NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. MOVE CONTAINERS FROM FIRE AREA IF THIS CAN BE DONE WITHOUT RISK. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS:  
FIRE-FIGHTERS SHOULD WEAR APPROPRIATE PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS (SCBA) WITH A FULL FACE-PIECE OPERATED IN POSITIVE PRESSURE MODE.

| REMARK: FLAMMABLE AEROSOL.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

FOR NON-EMERGENCY PERSONNEL:

NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. EVACUATE SURROUNDING AREAS. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. IN THE CASE OF AEROSOLS BEING RUPTURED, CARE SHOULD BE TAKEN DUE TO THE RAPID ESCAPE OF THE PRESSURIZED CONTENTS AND PROPELLANT. IF A LARGE NUMBER OF CONTAINERS ARE RUPTURED, TREAT AS A BULK MATERIAL SPILLAGE ACCORDING TO THE INSTRUCTIONS IN THE CLEAN-UP SECTION. DO NOT TOUCH OR WALK THROUGH SPILLED MATERIAL. SHUT OFF ALL IGNITION SOURCES. NO FLARES, SMOKING OR FLAMES IN HAZARD AREA. AVOID BREATHING VAPOR OR MIST. PROVIDE ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

FOR EMERGENCY RESPONDERS:

IF SPECIALIZED CLOTHING IS REQUIRED TO DEAL WITH THE SPILLAGE, TAKE NOTE OF ANY INFORMATION IN SECTION 8 ON SUITABLE AND UNSUITABLE MATERIALS. SEE ALSO THE INFORMATION IN "FOR NON-EMERGENCY PERSONNEL".

ENVIRONMENTAL PRECAUTIONS:

AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF AND CONTACT WITH SOIL, WATERWAYS, DRAINS AND SEWERS. INFORM THE RELEVANT AUTHORITIES IF THE PRODUCT HAS CAUSED ENVIRONMENTAL POLLUTION (SEWERS, WATERWAYS, SOIL OR AIR).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

SMALL SPILL:

STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. USE SPARK-PROOF TOOLS AND EXPLOSION-PROOF EQUIPMENT. DILUTE WITH WATER AND MOP UP IF WATER-SOLUBLE. ALTERNATIVELY, OR IF WATER-INSOLUBLE, ABSORB WITH AN INERT DRY MATERIAL AND PLACE IN AN APPROPRIATE WASTE DISPOSAL CONTAINER. DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR.

LARGE SPILL:

STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. USE SPARK-PROOF TOOLS AND EXPLOSION-PROOF EQUIPMENT. APPROACH RELEASE FROM UPWIND. PREVENT ENTRY INTO SEWERS, WATER COURSES, BASEMENTS OR CONFINED AREAS. WASH



SPILLAGES INTO AN EFFLUENT TREATMENT PLANT OR PROCEED AS FOLLOWS. CONTAIN AND COLLECT SPILLAGE WITH NON-COMBUSTIBLE, ABSORBENT MATERIAL E.G. SAND, EARTH, VERMICULITE OR DIATOMACEOUS EARTH AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR. CONTAMINATED ABSORBENT MATERIAL MAY POSE THE SAME HAZARD AS THE SPILLED PRODUCT.

**NOTE:**

SEE SECTION 1 FOR EMERGENCY CONTACT INFORMATION AND SECTION 13 FOR WASTE DISPOSAL.

## **SECTION 7. HANDLING AND STORAGE**

**PRECAUTIONS FOR SAFE HANDLING:**

**PROTECTIVE MEASURES:**

PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT (SEE SECTION 8). PERSONS WITH A HISTORY OF SKIN SENSITIZATION PROBLEMS SHOULD NOT BE EMPLOYED IN ANY PROCESS IN WHICH THIS PRODUCT IS USED.

**PRESSURIZED CONTAINER:**

PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C. DO NOT PIERCE OR BURN, EVEN AFTER USE. AVOID EXPOSURE - OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. AVOID EXPOSURE DURING PREGNANCY. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. DO NOT GET IN EYES OR ON SKIN OR CLOTHING. DO NOT BREATHE VAPOR OR MIST. DO NOT SWALLOW. AVOID BREATHING GAS. USE ONLY WITH ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. STORE AND USE AWAY FROM HEAT, SPARKS, OPEN FLAME OR ANY OTHER IGNITION SOURCE. USE EXPLOSION-PROOF ELECTRICAL (VENTILATING, LIGHTING AND MATERIAL HANDLING) EQUIPMENT. USE ONLY NON-SPARKING TOOLS. EMPTY CONTAINERS RETAIN PRODUCT RESIDUE AND CAN BE HAZARDOUS.

**ADVICE ON GENERAL OCCUPATIONAL HYGIENE:**

EATING, DRINKING AND SMOKING SHOULD BE PROHIBITED IN AREAS WHERE THIS MATERIAL IS HANDLED, STORED AND PROCESSED. WORKERS SHOULD WASH HANDS AND FACE BEFORE EATING, DRINKING AND SMOKING. REMOVE CONTAMINATED CLOTHING AND PROTECTIVE EQUIPMENT BEFORE ENTERING EATING AREAS. SEE ALSO SECTION 8 FOR ADDITIONAL INFORMATION ON HYGIENE MEASURES.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**

STORE IN ACCORDANCE WITH LOCAL REGULATIONS. STORE AWAY FROM DIRECT SUNLIGHT IN A DRY, COOL AND WELL-VENTILATED AREA, AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10) AND FOOD AND DRINK. PROTECT FROM SUNLIGHT. STORE LOCKED UP. ELIMINATE ALL IGNITION SOURCES. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION. SEE SECTION 10 FOR INCOMPATIBLE MATERIALS BEFORE HANDLING OR USE.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**CONTROL PARAMETERS:**

OCCUPATIONAL EXPOSURE LIMITS (OSHA UNITED STATES):

INGREDIENT NAME	CAS #	EXPOSURE LIMITS
ACETONE	67-64-1	<p>ACGIH TLV (UNITED STATES, 1/2022). TWA: 250 PPM 8 HOURS. STEL: 500 PPM 15 MINUTES.</p> <p>NIOSH REL (UNITED STATES, 10/2020). TWA: 250 PPM 10 HOURS. TWA: 590 MG/M3 10 HOURS.</p> <p>OSHA PEL (UNITED STATES, 5/2018). TWA: 1000 PPM 8 HOURS. TWA: 2400 MG/M3 8 HOURS.</p>
PROPANE	74-98-6	<p>NIOSH REL (UNITED STATES, 10/2020). TWA: 1000 PPM 10 HOURS. TWA: 1800 MG/M3 10 HOURS.</p> <p>OSHA PEL (UNITED STATES, 5/2018). TWA: 1000 PPM 8 HOURS. TWA: 1800 MG/M3 8 HOURS.</p> <p>ACGIH TLV (UNITED STATES, 1/2022). OXYGEN DEPLETION [ASPHYXIAN]. EXPLOSIVE POTENTIAL.</p>
BUTANE	106-97-8	<p>NIOSH REL (UNITED STATES, 10/2020). TWA: 800 PPM 10 HOURS. TWA: 1900 MG/M3 10 HOURS.</p> <p>ACGIH TLV (UNITED STATES, 1/2022). [BUTANE] EXPLOSIVE POTENTIAL. STEL: 1000 PPM 15 MINUTES.</p>
TOLUENE	108-88-3	<p>OSHA PEL Z2 (UNITED STATES, 2/2013). TWA: 200 PPM 8 HOURS. CEIL: 300 PPM AMP: 500 PPM 10 MINUTES.</p> <p>NIOSH REL (UNITED STATES, 10/2020). TWA: 100 PPM 10 HOURS. TWA: 375 MG/M3 10 HOURS.</p> <p>STEL: 150 PPM 15 MINUTES. STEL: 560 MG/M3 15 MINUTES.</p> <p>ACGIH TLV (UNITED STATES, 1/2022). OTOTOXICANT. TWA: 20 PPM 8 HOURS.</p>
ISOBUTYL ACETATE	110-19-0	<p>NIOSH REL (UNITED STATES, 10/2020). TWA: 150 PPM 10 HOURS. TWA: 700 MG/M3 10 HOURS.</p>

OSHA PEL (UNITED STATES, 5/2018).  
TWA: 150 PPM 8 HOURS.  
TWA: 700 MG/M3 8 HOURS.

ACGIH TLV (UNITED STATES, 1/2022).  
[BUTYL ACETATES]  
STEL: 150 PPM 15 MINUTES.  
TWA: 50 PPM 8 HOURS.

ETHYL 763-69-9 NONE.  
3-ETHOXYPROPIONATE

TRIMETHYLPENTANEDIOL 6846-50-0 NONE.  
DIISOBUTYRATE

TITANIUM DIOXIDE 13463-67-7 OSHA PEL (UNITED STATES, 5/2018).  
TWA: 15 MG/M3 8 HOURS.  
FORM: TOTAL DUST  
  
ACGIH TLV (UNITED STATES, 1/2022).  
TWA: 2.5 MG/M3 8 HOURS.  
  
FORM:  
RESPIRABLE FRACTION, FINESCALE  
PARTICLES

METHYL ETHYL KETOXIME 96-29-7 OARS WEEL (UNITED STATES, 1/2021).  
SKIN SENSITIZER.  
TWA: 10 PPM 8 HOURS.

OCCUPATIONAL EXPOSURE LIMITS (CANADA):

INGREDIENT NAME	CAS #	EXPOSURE LIMITS
ACETONE	67-64-1	CA ALBERTA PROVINCIAL (CANADA, 6/2018). 8 HRS OEL: 1200 MG/M3 8 HOURS. 15 MIN OEL: 1800 MG/M3 15 MINUTES.  8 HRS OEL: 500 PPM 8 HOURS. 15 MIN OEL: 750 PPM 15 MINUTES.  CA BRITISH COLUMBIA PROVINCIAL (CANADA, 3/2022). TWA: 250 PPM 8 HOURS. STEL: 500 PPM 15 MINUTES.  CA ONTARIO PROVINCIAL (CANADA, 6/2019). TWA: 250 PPM 8 HOURS. STEL: 500 PPM 15 MINUTES.  CA QUEBEC PROVINCIAL (CANADA, 6/2021). TWA EV: 500 PPM 8 HOURS. TWA EV: 1190 MG/M3 8 HOURS.  STEV: 1000 PPM 15 MINUTES. STEV: 2380 MG/M3 15 MINUTES.

		CA SASKATCHEWAN PROVINCIAL (CANADA, 7/2013). STEL: 750 PPM 15 MINUTES. TWA: 500 PPM 8 HOURS.
NORMAL PROPANE	74-98-6	CA ALBERTA PROVINCIAL (CANADA, 6/2018). 8 HRS OEL: 1000 PPM 8 HOURS.  CA QUEBEC PROVINCIAL (CANADA, 6/2021). TWA EV: 1000 PPM 8 HOURS. TWA EV: 1800 MG/M3 8 HOURS.  CA SASKATCHEWAN PROVINCIAL (CANADA, 7/2013). STEL: 1250 PPM 15 MINUTES. TWA: 1000 PPM 8 HOURS.  CA BRITISH COLUMBIA PROVINCIAL (CANADA, 3/2022). OXYGEN DEPLETION [ASPHYXIAN]. EXPLOSIVE POTENTIAL.  CA ONTARIO PROVINCIAL (CANADA, 6/2019). OXYGEN DEPLETION [ASPHYXIAN]. EXPLOSIVE POTENTIAL.
BUTANE	106-97-8	CA ALBERTA PROVINCIAL (CANADA, 6/2018). 8 HRS OEL: 1000 PPM 8 HOURS.  CA QUEBEC PROVINCIAL (CANADA, 6/2021). TWA EV: 800 PPM 8 HOURS. TWA EV: 1900 MG/M3 8 HOURS.  CA SASKATCHEWAN PROVINCIAL (CANADA, 7/2013). [BUTANE] STEL: 1250 PPM 15 MINUTES. TWA: 1000 PPM 8 HOURS.  CA BRITISH COLUMBIA PROVINCIAL (CANADA, 3/2022). [BUTANE, ALL ISOMERS] EXPLOSIVE POTENTIAL. STEL: 1000 PPM 15 MINUTES.  CA ONTARIO PROVINCIAL (CANADA, 6/2019). [BUTANE, ALL ISOMERS] EXPLOSIVE POTENTIAL. STEL: 1000 PPM 15 MINUTES.
TOLUENE	108-88-3	CA ALBERTA PROVINCIAL (CANADA, 6/2018). ABSORBED THROUGH SKIN. 8 HRS OEL: 50 PPM 8 HOURS. 8 HRS OEL: 188 MG/M3 8 HOURS.  CA BRITISH COLUMBIA PROVINCIAL (CANADA, 3/2022). TWA: 20 PPM 8 HOURS.  CA ONTARIO PROVINCIAL (CANADA, 6/2019).

		TWA: 20 PPM 8 HOURS.
		CA QUEBEC PROVINCIAL (CANADA, 6/2021). ABSORBED THROUGH SKIN. TWA EV: 50 PPM 8 HOURS. TWA EV: 188 MG/M3 8 HOURS.
		CA SASKATCHEWAN PROVINCIAL (CANADA, 7/2013). ABSORBED THROUGH SKIN. STEL: 60 PPM 15 MINUTES. TWA: 50 PPM 8 HOURS.
ISOBUTYL ACETATE	110-19-0	CA ALBERTA PROVINCIAL (CANADA, 6/2018). 8 HRS OEL: 150 PPM 8 HOURS. 8 HRS OEL: 713 MG/M3 8 HOURS.
		CA SASKATCHEWAN PROVINCIAL (CANADA, 7/2013). STEL: 188 PPM 15 MINUTES. TWA: 150 PPM 8 HOURS.
		CA ONTARIO PROVINCIAL (CANADA, 6/2019). [BUTYL ACETATES, ALL ISOMERS] STEL: 150 PPM 15 MINUTES. TWA: 50 PPM 8 HOURS.
		CA BRITISH COLUMBIA PROVINCIAL (CANADA, 3/2022). [BUTYL ACETATE, ALL ISOMERS] STEL: 150 PPM 15 MINUTES. TWA: 50 PPM 8 HOURS.
		CA QUEBEC PROVINCIAL (CANADA, 6/2021). [BUTYL ACETATES] STEL: 150 PPM 15 MINUTES. TWA EV: 50 PPM 8 HOURS.
TITANIUM DIOXIDE	13463-67-7	CA BRITISH COLUMBIA PROVINCIAL (CANADA, 3/2022). TWA: 10 MG/M3 8 HOURS. FORM: TOTAL DUST
		TWA: 3 MG/M3 8 HOURS. FORM: RESPIRABLE FRACTION
		CA QUEBEC PROVINCIAL (CANADA, 6/2021). TWA EV: 10 MG/M3 8 HOURS. FORM: TOTAL DUST.
		CA ALBERTA PROVINCIAL (CANADA, 6/2018). 8 HRS OEL: 10 MG/M3 8 HOURS.
		CA ONTARIO PROVINCIAL (CANADA, 6/2019). TWA: 10 MG/M3 8 HOURS.
		CA SASKATCHEWAN PROVINCIAL

(CANADA, 7/2013).  
STEL: 20 MG/M3 15 MINUTES.  
TWA: 10 MG/M3 8 HOURS.

METHYL ETHYL KETOXIME	96-29-7	OARS WHEEL (UNITED STATES, 1/2021). SKIN SENSITIZER. TWA: 10 PPM 8 HOURS.
--------------------------	---------	---

OCCUPATIONAL EXPOSURE LIMITS (MEXICO):

	CAS #	EXPOSURE LIMITS
ACETONE	67-64-1	NOM-010-STPS-2014 (MEXICO, 4/2016). TWA: 500 PPM 8 HOURS. STEL: 750 PPM 15 MINUTES.
PROPANE	74-98-6	NOM-010-STPS-2014 (MEXICO, 4/2016). TWA: 1000 PPM 8 HOURS.
BUTANE	106-97-8	NOM-010-STPS-2014 (MEXICO, 4/2016). TWA: 1000 PPM 8 HOURS.
TOLUENE	108-88-3	NOM-010-STPS-2014 (MEXICO, 4/2016). TWA: 20 PPM 8 HOURS.
ISOBUTYL ACETATE	110-19-0	NOM-010-STPS-2014 (MEXICO, 4/2016). TWA: 150 PPM 8 HOURS.

APPROPRIATE ENGINEERING CONTROLS:  
USE ONLY WITH ADEQUATE VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO KEEP WORKER EXPOSURE TO AIRBORNE CONTAMINANTS BELOW ANY RECOMMENDED OR STATUTORY LIMITS. THE ENGINEERING CONTROLS ALSO NEED TO KEEP GAS, VAPOR OR DUST CONCENTRATIONS BELOW ANY LOWER EXPLOSIVE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

ENVIRONMENTAL EXPOSURE CONTROLS:  
EMISSIONS FROM VENTILATION OR WORK PROCESS EQUIPMENT SHOULD BE CHECKED TO ENSURE THEY COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION LEGISLATION. IN SOME CASES, FUME SCRUBBERS, FILTERS OR ENGINEERING MODIFICATIONS TO THE PROCESS EQUIPMENT WILL BE NECESSARY TO REDUCE EMISSIONS TO ACCEPTABLE LEVELS.

INDIVIDUAL PROTECTION MEASURES:

HYGIENE MEASURES:  
WASH HANDS, FOREARMS AND FACE THOROUGHLY AFTER HANDLING CHEMICAL PRODUCTS, BEFORE EATING, SMOKING AND USING THE LAVATORY AND AT THE END OF THE WORKING PERIOD. APPROPRIATE TECHNIQUES SHOULD BE USED TO REMOVE POTENTIALLY CONTAMINATED CLOTHING. CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE. WASH CONTAMINATED CLOTHING BEFORE REUSING. ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE CLOSE TO THE WORKSTATION LOCATION.

EYE/FACE PROTECTION:  
SAFETY EYEWEAR COMPLYING WITH AN APPROVED STANDARD SHOULD BE USED WHEN A RISK ASSESSMENT INDICATES THIS IS NECESSARY TO AVOID EXPOSURE TO LIQUID SPLASHES, MISTS, GASES OR DUSTS. IF CONTACT IS POSSIBLE, THE FOLLOWING

PROTECTION SHOULD BE WORN, UNLESS THE ASSESSMENT INDICATES A HIGHER DEGREE OF PROTECTION: CHEMICAL SPLASH GOGGLES.

SKIN PROTECTION:

HAND PROTECTION:

CHEMICAL-RESISTANT, IMPERVIOUS GLOVES COMPLYING WITH AN APPROVED STANDARD SHOULD BE WORN AT ALL TIMES WHEN HANDLING CHEMICAL PRODUCTS IF A RISK ASSESSMENT INDICATES THIS IS NECESSARY. CONSIDERING THE PARAMETERS SPECIFIED BY THE GLOVE MANUFACTURER, CHECK DURING USE THAT THE GLOVES ARE STILL RETAINING THEIR PROTECTIVE PROPERTIES. IT SHOULD BE NOTED THAT THE TIME TO BREAKTHROUGH FOR ANY GLOVE MATERIAL MAY BE DIFFERENT FOR DIFFERENT GLOVE MANUFACTURERS. IN THE CASE OF MIXTURES, CONSISTING OF SEVERAL SUBSTANCES, THE PROTECTION TIME OF THE GLOVES CANNOT BE ACCURATELY ESTIMATED.

BODY PROTECTION:

PERSONAL PROTECTIVE EQUIPMENT FOR THE BODY SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT. WHEN THERE IS A RISK OF IGNITION FROM STATIC ELECTRICITY, WEAR ANTISTATIC PROTECTIVE CLOTHING. FOR THE GREATEST PROTECTION FROM STATIC DISCHARGES, CLOTHING SHOULD INCLUDE ANTI-STATIC OVERALLS, BOOTS AND GLOVES.

OTHER SKIN PROTECTION:

APPROPRIATE FOOTWEAR AND ANY ADDITIONAL SKIN PROTECTION MEASURES SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT.

RESPIRATORY PROTECTION:

BASED ON THE HAZARD AND POTENTIAL FOR EXPOSURE, SELECT A RESPIRATOR THAT MEETS THE APPROPRIATE STANDARD OR CERTIFICATION. RESPIRATORS MUST BE USED ACCORDING TO A RESPIRATORY PROTECTION PROGRAM TO ENSURE PROPER FITTING, TRAINING, AND OTHER IMPORTANT ASPECTS OF USE.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

THE CONDITIONS OF MEASUREMENT OF ALL PROPERTIES ARE AT STANDARD TEMPERATURE AND PRESSURE UNLESS OTHERWISE INDICATED.

APPEARANCE:

PHYSICAL STATE: LIQUID.

COLOR: NOT AVAILABLE.

ODOR: NOT AVAILABLE.

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT APPLICABLE.

MELTING POINT/FREEZING POINT: NOT AVAILABLE.

BOILING POINT, INITIAL BOILING POINT, AND BOILING RANGE: NOT AVAILABLE.

FLASH POINT:

CLOSED CUP: -29 DEG. C (-20.2 DEG. F) [PENSKEY-MARTENS CLOSED CUP]

EVAPORATION RATE: 5.6 (BUTYL ACETATE = 1)

| FLAMMABILITY: FLAMMABLE AEROSOL.

LOWER AND UPPER EXPLOSION LIMIT/FLAMMABILITY LIMIT:

LOWER: 1%

UPPER: 12.8%

VAPOR PRESSURE: 101.3 KPA (760 MMHg)

RELATIVE VAPOR DENSITY: 1.55 [AIR = 1]

RELATIVE DENSITY: 0.72

SOLUBILITY(IES):

MEDIA

RESULT

| COLD WATER

NOT SOLUBLE

PARTITION COEFFICIENT N-OCTANOL/WATER: NOT APPLICABLE.

AUTO-IGNITION TEMPERATURE: NOT AVAILABLE.

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

VISCOSITY:

KINEMATIC (40 DEG. C (104 DEG. F)): <20.5 MM<sup>2</sup>/S (<20.5 CST)

MOLECULAR WEIGHT: NOT APPLICABLE.

AEROSOL PRODUCT:

TYPE OF AEROSOL: SPRAY

HEAT OF COMBUSTION: 29.618 KJ/G

## **SECTION 10. STABILITY AND REACTIVITY**

REACTIVITY:

NO SPECIFIC TEST DATA RELATED TO REACTIVITY AVAILABLE FOR THIS PRODUCT OR ITS INGREDIENTS.

CHEMICAL STABILITY: THE PRODUCT IS STABLE.

POSSIBILITY OF HAZARDOUS REACTIONS:

UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS REACTIONS WILL NOT OCCUR.

CONDITIONS TO AVOID:

AVOID ALL POSSIBLE SOURCES OF IGNITION (SPARK OR FLAME).



INCOMPATIBLE MATERIALS: NO SPECIFIC DATA.

HAZARDOUS DECOMPOSITION PRODUCTS:  
UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS DECOMPOSITION  
PRODUCTS SHOULD NOT BE PRODUCED.

## SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
ACETONE	LD50 ORAL	RAT	5800 MG/KG	
BUTANE	LC50 INHALATION VAPOR	RAT	658000 MG/M3	4 HOURS
TOLUENE	LC50 INHALATION VAPOR LD50 ORAL	RAT RAT	49 G/M3 636 MG/KG	4 HOURS
ISOBUTYL ACETATE	LD50 DERMAL LD50 ORAL	RABBIT RAT	>17400 MG/KG 13400 MG/KG	
ETHYL 3-ETHOXYPROPIONATE	LD50 ORAL	RAT	3200 MG/KG	
METHYL ETHYL KETOXIME	LD50 ORAL	RAT	930 MG/KG	

IRRITATION/CORROSION:

PRODUCT/ INGREDIENT NAME	RESULT	SPECIES	SCORE	EXPOSURE	OBSERVATION
ACETONE	EYES: MILD IRRITANT	HUMAN		186300 PPM	
	EYES: MILD IRRITANT	RABBIT		10 UL	
	EYES: MODERATE IRRITANT	RABBIT		24 HOURS 20 MG	
	EYES: SEVERE IRRITANT	RABBIT		20 MG	
	SKIN: MILD IRRITANT	RABBIT		395 MG	

	SKIN:	RABBIT	24 HOURS
	MILD IRRITANT		500 MG
TOLUENE	EYES:	RABBIT	0.5 MINUTES
	MILD IRRITANT		100 MG
	EYES:	RABBIT	870 UG
	MILD IRRITANT		
	EYES:	RABBIT	24 HOURS
	SEVERE		2 MG
	IRRITANT		
	SKIN:	PIG	24 HOURS
	MILD IRRITANT		250 UL
	SKIN:	RABBIT	435 MG
	MILD IRRITANT		
	SKIN:	RABBIT	24 HOURS
	MODERATE		20 MG
	IRRITANT		
	SKIN:	RABBIT	500 MG
	MODERATE		
	IRRITANT		
ISOBUTYL	EYES:	RABBIT	24 HOURS
ACETATE	MODERATE		500 MG
	IRRITANT		
	SKIN:	RABBIT	500 MG
	MILD IRRITANT		
	SKIN:	RABBIT	24 HOURS
	MODERATE		500 MG
	IRRITANT		
ETHYL	SKIN:	RABBIT	24 HOURS
3-ETHOXY-	MILD IRRITANT		500 MG
PROPIONATE			
TRIMETHYL-	SKIN:	GUINEA	5 G
PENTANEDIOL	MILD IRRITANT	PIG	
DIISOBUTYRATE			
	SKIN:	HUMAN	504 HOURS
	MILD IRRITANT		1% I
TITANIUM	SKIN:	HUMAN	72 HOURS
DIOXIDE	MILD IRRITANT		300 UG I
METHYL ETHYL	EYES:	RABBIT	100 UL
KETOXIME	SEVERE		
	IRRITANT		

SENSITIZATION: NOT AVAILABLE.

MUTAGENICITY: NOT AVAILABLE.

CARCINOGENICITY: NOT AVAILABLE.

CLASSIFICATION:

PRODUCT/INGREDIENT NAME	OSHA	IARC	NTP
TOLUENE		3	
TITANIUM DIOXIDE		2B	

REPRODUCTIVE TOXICITY: NOT AVAILABLE.

TERATOGENICITY: NOT AVAILABLE.

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE):

NAME	CATEGORY	ROUTE OF EXPOSURE	TARGET ORGANS
ACETONE	CATEGORY 3		RESPIRATORY TRACT IRRITATION
	CATEGORY 3		NARCOTIC EFFECTS
PROPANE	CATEGORY 3		RESPIRATORY TRACT IRRITATION
	CATEGORY 3		NARCOTIC EFFECTS
BUTANE	CATEGORY 3		RESPIRATORY TRACT IRRITATION
	CATEGORY 3		NARCOTIC EFFECTS
TOLUENE	CATEGORY 3		RESPIRATORY TRACT IRRITATION
	CATEGORY 3		NARCOTIC EFFECTS
ISOBUTYL ACETATE	CATEGORY 3		NARCOTIC EFFECTS
METHYL ETHYL KETOXIME	CATEGORY 1		UPPER RESPIRATORY TRACT
	CATEGORY 3		NARCOTIC EFFECTS

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE):

NAME	CATEGORY	ROUTE OF EXPOSURE	TARGET ORGANS
ACETONE	CATEGORY 2		
PROPANE	CATEGORY 2		
BUTANE	CATEGORY 2		

TOLUENE CATEGORY 2

METHYL ETHYL KETOXIME CATEGORY 2 BLOOD SYSTEM

ASPIRATION HAZARD:

NAME	RESULT
------	--------

PROPANE	ASPIRATION HAZARD - CATEGORY 1
---------	--------------------------------

BUTANE	ASPIRATION HAZARD - CATEGORY 1
--------	--------------------------------

TOLUENE	ASPIRATION HAZARD - CATEGORY 1
---------	--------------------------------

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE: NOT AVAILABLE.

POTENTIAL ACUTE HEALTH EFFECTS:

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION.

INHALATION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE RESPIRATORY IRRITATION.

SKIN CONTACT: CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.

INGESTION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

EYE CONTACT:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

PAIN OR IRRITATION  
WATERING  
REDNESS

INHALATION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

RESPIRATORY TRACT IRRITATION  
COUGHING  
NAUSEA OR VOMITING  
HEADACHE  
DROWSINESS/FATIGUE  
DIZZINESS/VERTIGO  
UNCONSCIOUSNESS  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

SKIN CONTACT:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

IRRITATION

REDNESS

REDUCED FETAL WEIGHT

INCREASE IN FETAL DEATHS

SKELETAL MALFORMATIONS

INGESTION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

NAUSEA OR VOMITING

REDUCED FETAL WEIGHT

INCREASE IN FETAL DEATHS

SKELETAL MALFORMATIONS

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE:

SHORT TERM EXPOSURE:

POTENTIAL IMMEDIATE EFFECTS: NOT AVAILABLE.

POTENTIAL DELAYED EFFECTS: NOT AVAILABLE.

LONG TERM EXPOSURE:

POTENTIAL IMMEDIATE EFFECTS: NOT AVAILABLE.

POTENTIAL DELAYED EFFECTS: NOT AVAILABLE.

POTENTIAL CHRONIC HEALTH EFFECTS: NOT AVAILABLE.

GENERAL:

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. ONCE SENSITIZED, A SEVERE ALLERGIC REACTION MAY OCCUR WHEN SUBSEQUENTLY EXPOSED TO VERY LOW LEVELS.

CARCINOGENICITY:

SUSPECTED OF CAUSING CANCER. RISK OF CANCER DEPENDS ON DURATION AND LEVEL OF EXPOSURE.

MUTAGENICITY: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

TERATOGENICITY: SUSPECTED OF DAMAGING THE UNBORN CHILD.

DEVELOPMENTAL EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

FERTILITY EFFECTS: SUSPECTED OF DAMAGING FERTILITY.

NUMERICAL MEASURES OF TOXICITY:

ACUTE TOXICITY ESTIMATES:

ROUTE	ATE VALUE
-------	-----------

ORAL	5361.7 MG/KG
------	--------------

## **SECTION 12. ECOLOGICAL INFORMATION**

## TOXICITY:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	EXPOSURE
ACETONE	ACUTE EC50: 7200000 (MICRO)G/L FRESH WATER	ALGAE - SELENASTRUM SP.	96 HOURS
	ACUTE LC50: 4.42589 ML/L MARINE WATER	CRUSTACEANS - ACARTIA TONSA - COPEPODID	48 HOURS
	ACUTE LC50: 7460000 (MICRO)G/L FRESH WATER	DAPHNIA - DAPHNIA CUCULLATA	48 HOURS
	ACUTE LC50: 5600 PPM FRESH WATER	FISH - POECILIA RETICULATA	96 HOURS
	CHRONIC NOEC: 4.95 MG/L MARINE WATER	ALGAE - ULVA PERTUSA	96 HOURS
	CHRONIC NOEC: 0.016 ML/L FRESH WATER	CRUSTACEANS - DAPHNIIDAE	21 DAYS
	CHRONIC NOEC: 0.1 ML/L FRESH WATER	DAPHNIA - DAPHNIA MAGNA - NEONATE	21 DAYS
	CHRONIC NOEC: 5 (MICRO)G/L MARINE WATER	FISH - GASTEROSTEUS ACULEATUS - LARVAE	42 DAYS
TOLUENE	ACUTE EC50: >433 PPM MARINE WATER	ALGAE - SKELETONEMA COSTATUM	96 HOURS
	ACUTE EC50: 11600 (MICRO)G/L FRESH WATER	CRUSTACEANS - GAMMARUS PSEUDOLIMNAEUS - ADULT	48 HOURS
	ACUTE EC50: 6000 (MICRO)G/L FRESH WATER	DAPHNIA - DAPHNIA MAGNA - JUVENILE (FLEDGLING, HATCHLING, WEANLING)	48 HOURS
	ACUTE LC50: 5500 (MICRO)G/L FRESH WATER	FISH - ONCORHYNCHUS KISUTCH - FRY	96 HOURS
	CHRONIC NOEC:	DAPHNIA - DAPHNIA	21 DAYS

	1 MG/L FRESH WATER	MAGNA	
TITANIUM DIOXIDE	ACUTE LC50: >1000000 (MICRO)G/L MARINE WATER	FISH - FUNDULUS HETEROCLITUS	96 HOURS
METHYL ETHYL KETOXIME	ACUTE LC50: 843000 (MICRO)G/L FRESH WATER	FISH - PIMEPHALES PROMELAS	96 HOURS

PERSISTENCE AND DEGRADABILITY:

PRODUCT/INGREDIENT NAME	AQUATIC HALF-LIFE	PHOTOLYSIS	BIODEGRADABILITY
ACETONE			READILY
TOLUENE			READILY

BIOACCUMULATIVE POTENTIAL:

PRODUCT/INGREDIENT NAME	LOGPOW	BCF	POTENTIAL
TOLUENE		90	LOW
TRIMETHYLPENTANEDIOL DIISOBUTYRATE		5340	HIGH
METHYL ETHYL KETOXIME		2.5 TO 5.8	LOW

MOBILITY IN SOIL:

SOIL/WATER PARTITION COEFFICIENT (KOC): NOT AVAILABLE.

OTHER ADVERSE EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

### SECTION 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

THE GENERATION OF WASTE SHOULD BE AVOIDED OR MINIMIZED WHEREVER POSSIBLE. DISPOSAL OF THIS PRODUCT, SOLUTIONS AND ANY BY-PRODUCTS SHOULD AT ALL TIMES COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL LEGISLATION AND ANY REGIONAL LOCAL AUTHORITY REQUIREMENTS. DISPOSE OF SURPLUS AND NON-RECYCLABLE PRODUCTS VIA A LICENSED WASTE DISPOSAL CONTRACTOR. WASTE SHOULD NOT BE DISPOSED OF UNTREATED TO THE SEWER UNLESS FULLY COMPLIANT WITH THE REQUIREMENTS OF ALL AUTHORITIES WITH JURISDICTION. WASTE PACKAGING SHOULD BE RECYCLED. INCINERATION OR LANDFILL SHOULD ONLY BE CONSIDERED WHEN RECYCLING IS NOT FEASIBLE. THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY. EMPTY CONTAINERS OR LINERS MAY RETAIN SOME PRODUCT RESIDUES. DO NOT PUNCTURE OR INCINERATE CONTAINER.

### SECTION 14. TRANSPORT INFORMATION

	DOT CLASSIFICATION	TDG CLASSIFICATION	MEXICO CLASSIFICATION
UN NUMBER	UN1950	UN1950	UN1950
UN PROPER SHIPPING NAME	AEROSOLS	AEROSOLS	AEROSOLS
TRANSPORT HAZARD CLASS(ES)	2.1 FLAMMABLE GAS, CLASS/DIVISION 2.1	2.1 CLASS 2.1, FLAMMABLE GASES	2.1 CLASS 2.1, FLAMMABLE GASES

PACKING GROUP

ENVIRONMENTAL HAZARDS	NO.	NO.	NO.
--------------------------	-----	-----	-----

ADDITIONAL  
INFORMATION

PRODUCT  
CLASSIFIED  
AS PER THE  
FOLLOWING  
SECTIONS OF THE  
TRANSPORTATION  
OF DANGEROUS  
GOODS  
REGULATIONS:  
2.13-2.17  
(CLASS 2).

ERG NO.: 126

ERG NO.: 126

ERG NO.: 126

DEPENDENT UPON  
CONTAINER SIZE,  
THIS PRODUCT MAY  
SHIP UNDER  
THE LIMITED  
QUANTITY SHIPPING  
EXCEPTION.

DEPENDENT UPON  
CONTAINER SIZE,  
THIS PRODUCT  
MAY SHIP UNDER  
THE LIMITED  
QUANTITY  
SHIPPING  
EXCEPTION.

DEPENDENT UPON  
CONTAINER SIZE,  
THIS PRODUCT  
MAY SHIP UNDER  
THE LIMITED  
QUANTITY  
SHIPPING  
EXCEPTION.

	IATA	IMDG
UN NUMBER	UN1950	UN1950
UN PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE	AEROSOLS
TRANSPORT HAZARD CLASS(ES)	2.1 CLASS 2.1, FLAMMABLE GASES	2.1 CLASS 2.1 - FLAMMABLE GASES

PACKING GROUP

ENVIRONMENTAL HAZARDS	NO.	NO.
-----------------------	-----	-----

ADDITIONAL INFORMATION

EMERGENCY SCHEDULES:  
F-D, S-U



DEPENDENT UPON  
CONTAINER SIZE, THIS  
PRODUCT MAY SHIP UNDER  
THE LIMITED QUANTITY  
SHIPPING EXCEPTION.

DEPENDENT UPON  
CONTAINER SIZE, THIS  
PRODUCT MAY SHIP UNDER  
THE LIMITED QUANTITY  
SHIPPING EXCEPTION.

SPECIAL PRECAUTIONS FOR USER:

MULTI-MODAL SHIPPING DESCRIPTIONS ARE PROVIDED FOR INFORMATIONAL PURPOSES AND DO NOT CONSIDER CONTAINER SIZES. THE PRESENCE OF A SHIPPING DESCRIPTION FOR A PARTICULAR MODE OF TRANSPORT (SEA, AIR, ETC.), DOES NOT INDICATE THAT THE PRODUCT IS PACKAGED SUITABLY FOR THAT MODE OF TRANSPORT. ALL PACKAGING MUST BE REVIEWED FOR SUITABILITY PRIOR TO SHIPMENT, AND COMPLIANCE WITH THE APPLICABLE REGULATIONS IS THE SOLE RESPONSIBILITY OF THE PERSON OFFERING THE PRODUCT FOR TRANSPORT. PEOPLE LOADING AND UNLOADING DANGEROUS GOODS MUST BE TRAINED ON ALL OF THE RISKS DERIVING FROM THE SUBSTANCES AND ON ALL ACTIONS IN CASE OF EMERGENCY SITUATIONS.

TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS: NOT AVAILABLE.

PROPER SHIPPING NAME: NOT AVAILABLE.

## **SECTION 15. REGULATORY INFORMATION**

SARA 313:

SARA 313 (40 CFR 372.45) SUPPLIER NOTIFICATION CAN BE FOUND ON THE ENVIRONMENTAL DATA SHEET.

CALIFORNIA PROP. 65:

WARNING:

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INTERNATIONAL REGULATIONS:

INTERNATIONAL LISTS:

AUSTRALIA INVENTORY (AIIC): NOT DETERMINED.

CHINA INVENTORY (IECSC): NOT DETERMINED.

JAPAN INVENTORY (CSCL): NOT DETERMINED.

JAPAN INVENTORY (ISHL): NOT DETERMINED.

KOREA INVENTORY (KECI): NOT DETERMINED.

NEW ZEALAND INVENTORY OF CHEMICALS (NZIOC): NOT DETERMINED.

PHILIPPINES INVENTORY (PICCS): NOT DETERMINED.

TAIWAN CHEMICAL SUBSTANCES INVENTORY (TCSI): NOT DETERMINED.

THAILAND INVENTORY: NOT DETERMINED.

TURKEY INVENTORY: NOT DETERMINED.

VIETNAM INVENTORY: NOT DETERMINED.

## **SECTION 16. OTHER INFORMATION**

HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.):  
HEALTH 3\*  
FLAMMABILITY 4  
PHYSICAL HAZARDS 3

THE CUSTOMER IS RESPONSIBLE FOR DETERMINING THE PPE CODE FOR THIS MATERIAL.  
FOR MORE INFORMATION ON HMIS(R\*) PERSONAL PROTECTIVE EQUIPMENT (PPE)  
CODES, CONSULT THE HMIS(R\*) IMPLEMENTATION MANUAL.

CAUTION:

HMIS(R\*) RATINGS ARE BASED ON A 0-4 RATING SCALE, WITH 0 REPRESENTING  
MINIMAL HAZARDS OR RISKS, AND 4 REPRESENTING SIGNIFICANT HAZARDS OR RISKS.  
ALTHOUGH HMIS(R\*) RATINGS AND THE ASSOCIATED LABEL ARE NOT REQUIRED ON SDSS  
OR PRODUCTS LEAVING A FACILITY UNDER 29 CFR 1910.1200, THE PREPARER MAY  
CHOOSE TO PROVIDE THEM. HMIS(R\*) RATINGS ARE TO BE USED WITH A FULLY  
IMPLEMENTED HMIS(R\*) PROGRAM. HMIS(R\*) IS A REGISTERED TRADEMARK AND  
SERVICE MARK OF THE AMERICAN COATINGS ASSOCIATION, INC.

PROCEDURE USED TO DERIVE THE CLASSIFICATION:

CLASSIFICATION	JUSTIFICATION
FLAMMABLE AEROSOLS - CATEGORY 1	ON BASIS OF TEST DATA
GASES UNDER PRESSURE - COMPRESSED GAS	CALCULATION METHOD
SKIN CORROSION/IRRITATION - CATEGORY 2	CALCULATION METHOD
SERIOUS EYE DAMAGE/EYE IRRITATION - CATEGORY 2A	CALCULATION METHOD
SKIN SENSITIZATION - CATEGORY 1	CALCULATION METHOD
CARCINOGENICITY - CATEGORY 2	CALCULATION METHOD
TOXIC TO REPRODUCTION - CATEGORY 2	CALCULATION METHOD
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (RESPIRATORY TRACT IRRITATION) - CATEGORY 3	CALCULATION METHOD
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (NARCOTIC EFFECTS) - CATEGORY 3	CALCULATION METHOD
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - CATEGORY 2	CALCULATION METHOD
ASPIRATION HAZARD - CATEGORY 1	CALCULATION METHOD

HISTORY:

DATE OF PRINTING: 11/23/2022

DATE OF ISSUE/DATE OF REVISION: 11/23/2022

DATE OF PREVIOUS ISSUE: 8/11/2022

VERSION: 16

KEY TO ABBREVIATIONS:

ATE: ACUTE TOXICITY ESTIMATE

BCF: BIOCONCENTRATION FACTOR

GHS:

GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS

IATA: INTERNATIONAL AIR TRANSPORT ASSOCIATION

IBC: INTERMEDIATE BULK CONTAINER

IMDG: INTERNATIONAL MARITIME DANGEROUS GOODS

LOGPOW: LOGARITHM OF THE OCTANOL/WATER PARTITION COEFFICIENT

MARPOL:

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973  
AS MODIFIED BY THE PROTOCOL OF 1978. ("MARPOL" = MARINE POLLUTION)

N/A: NOT AVAILABLE

SGG: SEGREGATION GROUP

UN: UNITED NATIONS

| INDICATES INFORMATION THAT HAS CHANGED FROM PREVIOUSLY ISSUED VERSION.

NOTICE TO READER:

IT IS RECOMMENDED THAT EACH CUSTOMER OR RECIPIENT OF THIS SAFETY DATA SHEET (SDS) STUDY IT CAREFULLY AND CONSULT RESOURCES, AS NECESSARY OR APPROPRIATE, TO BECOME AWARE OF AND UNDERSTAND THE DATA CONTAINED IN THIS SDS AND ANY HAZARDS ASSOCIATED WITH THE PRODUCT. THIS INFORMATION IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE ACCURATE AS OF THE EFFECTIVE DATE HEREIN. HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN. THE INFORMATION PRESENTED HERE APPLIES ONLY TO THE PRODUCT AS SHIPPED. THE ADDITION OF ANY MATERIAL CAN CHANGE THE COMPOSITION, HAZARDS AND RISKS OF THE PRODUCT. PRODUCTS SHALL NOT BE REPACKAGED, MODIFIED, OR TINTED EXCEPT AS SPECIFICALLY INSTRUCTED BY THE MANUFACTURER, INCLUDING BUT NOT LIMITED TO THE INCORPORATION OF PRODUCTS NOT SPECIFIED BY THE MANUFACTURER, OR THE USE OR ADDITION OF PRODUCTS IN PROPORTIONS NOT SPECIFIED BY THE MANUFACTURER. REGULATORY REQUIREMENTS ARE SUBJECT TO CHANGE AND MAY DIFFER BETWEEN VARIOUS LOCATIONS AND JURISDICTIONS. THE CUSTOMER/BUYER/USER IS RESPONSIBLE TO ENSURE THAT HIS ACTIVITIES COMPLY WITH ALL COUNTRY, FEDERAL, STATE, PROVINCIAL OR LOCAL LAWS. THE CONDITIONS FOR USE OF THE PRODUCT ARE NOT UNDER THE CONTROL OF THE MANUFACTURER; THE CUSTOMER/BUYER/USER IS RESPONSIBLE TO DETERMINE THE CONDITIONS NECESSARY FOR THE SAFE USE OF THIS PRODUCT. THE CUSTOMER/BUYER/USER SHOULD NOT USE THE PRODUCT FOR ANY PURPOSE OTHER THAN THE PURPOSE SHOWN IN THE APPLICABLE SECTION OF THIS SDS WITHOUT FIRST REFERRING TO THE SUPPLIER AND OBTAINING WRITTEN HANDLING INSTRUCTIONS. DUE TO THE PROLIFERATION OF SOURCES FOR INFORMATION SUCH AS MANUFACTURER-SPECIFIC SDS, THE MANUFACTURER CANNOT BE RESPONSIBLE FOR SDSS OBTAINED FROM ANY OTHER SOURCE.

SHW-85-NA-GHS-US

