

Apollo PowerPress coupling without stop (2 x press)



group: 401 category: fittings product line: Apollo PowerPress

applications

heating, cooling, compressed air, sprinkler

segments

fire protection , utility , industry

approvals

CRN , FM , IAPMO/ANSI/CAN Z1117 , ICC LC1002 , TSSA , UL , ULc

assortment

item code	size	dimensions	weight	packaging	gtin + upc
PWR7480066	1/2"	3.07x1.26x1.26 "	0.32 lb	Carton (10 pce)	08711985368871
PWR7480077	3/4"	3.27x1.50x1.50 "	0.41 lb	Carton (10 pce)	08711985368888
PWR7480088	1"	3.66x1.81x1.81 "	0.62 lb	Carton (5 pce)	08711985368895
PWR7480099	1 1/4"	4.65x2.20x2.20 "	0.97 lb	Carton (1 pce)	08711985368901
PWR7480101	1 1/2"	4.92x2.44x2.44 "	1.27 lb	Carton (1 pce)	08711985368918
PWR7480110	2"	5.12x2.91x2.91 "	1.65 lb	Carton (1 pce)	08711985368925

specifications - characteristics

color	grey
materials	steel (St 35 (1.0308))
finishing	zinc-nickel plated
manufacturer	Aalberts integrated piping systems B.V. (VSH)
shape	straight
connection type	press (DW)
sealing	EPDM

specifications - general

product group	fittings
ETIM class	EC003024 Fitting with 2 connections
intrastat code	73079980
country of origin	Netherlands
brand	Apollo
series	PowerPress
product type	401
unsps	40172602

dimensions

item code	size	d1	DN1	l1	z1	es1	d2	DN2	l2	z2	es2
PWR7480066	1/2"	0.84	DN15	1.55	0.45	1.10	0.84	DN15	1.55	0.45	1.10
PWR7480077	3/4"	1.05	DN20	1.64	0.42	1.22	1.05	DN20	1.64	0.42	1.22
PWR7480088	1"	1.32	DN25	1.84	0.42	1.42	1.32	DN25	1.84	0.42	1.42
PWR7480099	1 1/4"	1.66	DN32	2.34	0.45	1.89	1.66	DN32	2.34	0.45	1.89
PWR7480101	1 1/2"	1.90	DN40	2.50	0.57	1.93	1.90	DN40	2.50	0.57	1.93
PWR7480110	2"	2.37	DN50	2.56	0.48	2.09	2.37	DN50	2.56	0.48	2.09

