

## Eaton Bussmann series LP-CC fuse

**LP-CC-8/10**

**UPC:**051712180429

**Dimensions:**

- **Height:** .41 IN
- **Length:** 1.5 IN
- **Width:** .41 IN

**Weight:**.15 LB

**Warranties:**

- Not Applicable

**Specifications:**

- **Type:** Current-limiting, Time-delay
- **Special Features:** Rejection Style
- **Application:** Specialized circuits and industrial control
- **Voltage Rating:** 600 Vac, 300 Vdc
- **Amperage Rating:** 0.80A
- **Interrupt Rating:** 200 kAIC at 600 Vac, 20 kAIC at 150 Vdc
- **Class:** Class CC
- **Connection:** Ferrule end X ferrule end
- **Material Type:** Melamine tube
- **Packaging Type:** Standard
- **Diameter:** .40625 IN
- **Quantity:** Carton: 10
- **Fuse Indicator:** Non Indicating
- **Response Time:** 12s at 200%
- **Number Of Elements:** Dual

**Supporting documents:**

- [Product Catalog](#)
- [LOW PEAK CC TIME DELAY](#)

**Certifications:** No Data

**Product compliance:**

- CE Marked
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.