Impact Punchdown Tool

- · Includes full 110 and 66 blades
- Adjustable high/low actuation setting accommodates termination requirements
- Turn-Lock™ Style blade holding design
- Impact-absorbing cushioned grip reduces operator stress for high volume installers

Description	Part No.
Punchmaster™ II Punchdown Tool w/full 110 & 66 blades	35-485

Punchdown Tool Blades

Removable Blades	Part No.
110 Turn-Lock™ blade	35-495
66 Turn-Lock™ blade	35-497
110/66 combo blade w/cutting edges	35-407
Krone® blade	35-478
Bix® blade	35-479

Bix® is a registered trademark of Nortel. Krone® is a registered trademark of Krone. Inc.

Probe Pic & Spudger

 For isolating conductors and removing terminated wires from voice and data IDC contacts

Description	Part No.
Probe Pic & Spudger	35-473

RJ-11 Voice Modular Plugs

- 6 position plugs for use in traditional landline phone applications and other RJ-11/12 terminations
- Provides 1, 2 or 3 lines of service. 3 lines requires 85-345
- · 50 micron gold contacts
- Two versions available 6 contacts and 4 contacts

Description	Quantity	Part No.
6-Position 6-Contact, RJ-11 (RJ-12)	Card of 25	85-345
6-Position 4-Contact, RJ-11	Card of 25	85-344

Ratchet Telemaster[™] Modular Plug Crimping Tool

- Heavy-duty version of the 30-496 Telemaster[™] Tool
- Ratchet ensures full cycle crimping every time
- Crimps RJ-45 (8P8C) and RJ-11/12 (6P6C/6P4C) standard modular plugs
- Multi-function tool also cuts UTP/STP and strips CAT 5e/6 cable jacket and flat cable jackets
- Black oxide coated steel frame with cushioned handles for strength and comfort

Description	Part No.
Ratchet Telemaster™	30-696
Replacement Cut & Strip Blade Set	LA-4102

Telemaster™ Modular Plug Crimping Tool





- Multi-function tool also cuts UTP/STP and strips round CAT 5e/6 cable jacket
- Black oxide coated steel frame with cushioned handles for strength and comfort

Description	Replacement	Kit	Tool Only	
	Blade	Part No.	Part No.	
Telemaster™ Crimping Tool RJ-45 and RJ-11/12	LB-1747	33-700*	30-496	

*Kit includes 10 each, RJ-45 8P8C, RJ-11 6P6C and RJ-11 6P4C modular plugs.

Data/Voice Crimp Tool Kit

- Compact design is 2/3 the size of traditional crimp tools
- Crimps RJ-45 (8P8C) and RJ-11/12 (6P6C/6P4C) modular plugs



- One tool assembly process cut, strip and crimp connectors on to CAT 3/5e/6 cables
- Black oxide coated steel core with spring loaded handle and locking feature

Description	Part No.
Data/Voice Crimp Tool Kit includes ten RJ-11 (6P6C) and ten CAT5e RJ-45 plugs	33-396

Modular Plugs

	Name	САТ	Туре	Feed-Thru	Shielded	Notes	Quantity	Part No.	
							For shielded or unshielded CAT6A,	Card of 10	85-363
	CAT6A/6/5e Shield- ed Feed-Thru	Multi	RJ-45 8P8C	/	/	CAT6 or CAT5e with insulated conductor diameter of 0.040" to	Card of 25	85-368	
	ed reed-mid		OFOC			0.048", max. jacket diameter of .320"	Jar of 50	85-369	
	CAT6A/6 0.048" Feed-Thru	6A/6	RJ-45 8P8C	~		For unshielded CAT6A/6 with insulated conductor diameter of 0.040" to 0.048"; max jacket diameter of .320"	Card of 50	85-385	
						For unshielded CAT6 with	Card of 25	85-375	
	CAT6 Feed-Thru	6	RJ-45			23 or 24 AWG conductors with a max, insulated conductor	Card of 50	85-376	
	CATO Feed-IIIIu	0	8P8C			diameter of 0.041", max. jacket diameter of .290"	Bag of 100	85-377	
						diameter of .290	Jar of 100	85-377J	
A.						For unshielded CAT6 with	Card of 25	85-367	
	CAT6 Single Piece Standard	6	RJ-45 8P8C			23 or 24 AWG conductors with a max. insulated conductor	Card of 50	85-362	
	2 200 7 200 200					diameter of 0.041", max jacket diameter of .290"	Jar of 100	86-367J	
	CAT6 3-Piece Standard	6	RJ-45 8P8C			3 piece assembly of body, sled and liner. For unshielded CAT6 with 23 or 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .290"	Card of 25	85-366	
				-			Card of 25	85-370	
			RJ-45			For unshielded CAT5e with 23 or 24 AWG conductors with	Card of 50	85-371	
	CAT5e Feed-Thru	5e	8P8C			a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"	Bag of 100	85-372	
						jaoner alamotel et le	Jar of 100	85-3 72 J	
	CAT5e Shielded Feed-Thru	5e	RJ-45 8P8C	~	~	For shielded CAT5e with 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"	Card of 25	85-365	
	CAT5e Shielded	5e	RJ-45 8P8C		~	For shielded CAT5e with 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"	Card of 25	85-361	
							Card of 10	85-147	
	CAT5e Standard	rd 5e				For any highland CATE and the 27 and 27	Card of 15*	85-379	
An Anna			RJ-45			For unshielded CAT5e with 23 or 24 AWG conductors with a max.	Card of 25	85-346	
			8P8C	8P8C			insulated conductor diameter of 0.041", max. jacket diameter of .270"	Card of 50	85-396
							Bag of 100	86-396	
							Jar of 100	86-396J	
	Snaglass Strain Relief Boot	5e/6	RJ-45 8P8C			Blue color, slide on snagless boot, max. cable diameter of 5.5mm/.225"	Card of 25	85-380	
	6-Contact Voice Plug	3	RJ-11/12 6P6C			6-position, 6-contact voice grade modular plug, max. 24 AWG conductors	Card of 25	85-345	
	4-Contact Voice Plug	3	RJ-11 6P4C			6-position, 4-contact voice grade modular plug, max. 24 AWG conductors	Card of 25	85-344	

^{*}Includes 15 Strain Relief Boots