


2-gang toggle, standard size, metallic finish wallplate



FINISH	CAT. NO. / UPC
Chrome Plate	83072
Mirror	095327830720
Anodized	95072
Aluminum-Clear	095327950725
Stainless Steel-Type	93072
304-Satin	095327930727
Stainless Steel-Type	68072
304-Mirror	095327680721
Stainless Steel-Type	70072
304-Satin (.060 in.)	095327700726
Stainless Steel-Type	97072
430-Satin	095327970723
Statuary Bronze-	69072
Dark	095327690720

TECHNICAL INFORMATION

Material:

Type 304 Stainless Steel: Satin or Mirror finish, non-magnetic, .030 inches thick (except 70000 Series which measures .060 inches in thickness). This alloy contains 18% chromium and 8% nickel and offers superior resistance to corrosion. Ideal for hospitals, schools and other public institutions, as well as computer rooms.

Type 430 Stainless Steel: Satin finish, .030 inches thick. Good corrosion resistance, but, not as resistant as Type 304 nor does it have the same non-magnetic properties. Ideal for industrial and commercial applications in a less corrosive atmosphere.

Solid Brass: This distinctive copper / zinc alloy is available in Polished Brass, .040 inches thick, and, two grades of Satin Brass-one measuring .040 inches and the other, .060 inches in thickness. Polished Brass wallplates are packaged with protective film to inhibit oxidation. These superior brass wallplates will add a touch of warmth and elegance to any room.

Bronze: Available in Statuary Bronze, Bank Bronze and

Bank Bronze- Medium	65072 095327650724
Satin Brass	94072 095327940726
Satin Brass (.060 in.)	96072 095327960724
Satin Bronze	66072 095327660723
Polished Brass- Mirror	64072 095327640725

Satin Bronze, each .040 inches thick-providing a rich, decorative look.

Aluminum: Made of anodized aluminum, .040 inches thick, with a smooth finish. Appropriate for most commercial and industrial applications.

Chrome: Plated chrome with a mirror finish, .030 inches

thick.

Mechanical:

Gang: 2

Size: Standard (4.5 in. high x 4.562 in. wide)

Size / Shape: Standard **Opening:** (2) Toggle

Mounting: Device (2.375 in. between mounting holes)

Finishes: Available in a choice of (12) twelve finishes in stainless steel, brass, bronze, chrome and aluminum. Comes with 1/2 inch standard slotted 6-32 oval head screws in matching finishes.

Standards:

Applicable Standards: UL 514D

Certification: UL Listed

Product Features:

- Ideal for residential, commercial and institutional applications.
- Smooth, rounded edges prevent wall damage.
- Add elegance to any room in your home or office.
- Can be silk-screened or engraved.
- Made in the U.S.A.

Box Quantity: 10



www.mulberrymetal.com

Mulberry Metal Products, Inc., Union, New Jersey 07083