4" SQUARE DOUBLE GANG DEVICE RINGS









(ŮL



FEATURES

 Angled slots on the covers compensate for up to 12° of box misalignment on upright framing members

APPLICATIONS

 4" square two device rings are used with 4" square boxes to mount switches, receptacles and devices

STANDARD MATERIAL

• Galvanized steel or 316 stainless steel

CERTIFICATIONS

• UL, cULus Listed

PART #	DESCRIPTION	RAISED	CUBIC INCHES (CM ³)	MASTER QTY.
52C20A	FOR DRYWALL FINISH	FLAT		50
52C20		1/4"	3.0 (49.2)	50
52C17		1/2"	5.5 (90.1)	50
52C18-5/8		5/8"	7.3 (119.6)	50
52C18		3/4"	8.8 (144.2)	50
52C19		1"	12.0 (196.6)	25
52C21		1-1/4"	15.0 (245.8)	25
52C24		1-1/2"	15.5 (253.9)	25
52C25		2"	20.5 (335.9)	25
52C20A-SS	FOR DRYWALL FINISH, 316 STAINLESS STEEL	FLAT		50
52C20-SS		1/4"	3.0 (49.2)	50
52C17-SS		1/2"	5.5 (90.1)	50
52C18-SS		3/4"	7.3 (119.6)	50
52C19-SS		1"	12.0 (196.6)	25
52C21-SS		1-1/4"	15.0 (245.8)	25
52C24-SS		1-1/2"	15.5 (253.9)	25