



T8

8.5T8/MAS/36-835/IF13/P/DIM 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

General Information			
Base	G13 [Medium Bi-Pin Fluorescent]		
EU RoHS compliant	Yes		
Nominal Lifetime (Nom)	70000 h		
Switching Cycle	50000X		
Light Technical			
Color Code	835 [CCT of 3500K]		
Beam Angle (Nom)	180 °		
Initial lumen (Nom)	1350 lm		
Color Designation	White (WH)		
Correlated Color Temperature (Nom)	3500 K		
Luminous Efficacy (rated) (Nom)	152.00 lm/W		
Color Consistency	<6		
Color Rendering Index (Nom)	80		
LLMF At End Of Nominal Lifetime (Non	n) 70 %		
Operating and Electrical			
Input Frequency	20K to 120K Hz		
Power (Rated) (Nom)	8.5 W		


Starting Time (Nom)	0.5 s		
Starting Time (Nom)	0.5 3		
Warm Up Time to 60% Light (Nom)	0.5 s		
UL Type	Type A - works on ballast Type C - works with		
	dedicated LED driver Type A+C - works with		
	both ballasts and the LED driver		
Power Factor (Nom)	0.9		
Voltage (Nom)	120-277, 347 V		
Temperature			
T-Ambient (Max)	45 °C		
T-Ambient (Min)	-20 °C		
T-Storage (Max)	65 ℃		
T-Storage (Min)	-40 °C		
T-Case Maximum (Nom)	50 °C		
Controls and Dimming			
Dimmable	Yes		

Datasheet, 2021, February 28 data subject to change

Mechanical and Housing	
Product Length	36 in
Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC
	compliance
Energy Consumption kWh/1000 h	- kWh
Energy Certifications	DLC Standard


Product Data	
Order product name	8.5T8/MAS/36-835/IF13/P/DIM 10/
<u> </u>	
EAN/UPC - Product	046677539863
Order code	539866
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001967904
Net Weight (Piece)	0.160 kg
Model Number	9290019679


Dimensional drawing



Product	D1	D2	A1	A2	А3
8.5T8/MAS/36-835/	25.7 mm	26.3 mm	893.4 mm	900.5 mm	907.6 mm
IF13/P/DIM 10/1					

Photometric data






G13 3500K 1300lm


G13 3500K 1300lm


Photometric data




G13 4000K


Lifetime





G13 4000K






G13 4000K

G13 4000K

3

G13 4000K

Lifetime



G13 4000K

