## **DROPIN™** Floor Box Kits with Steel Bracket



## Fastest, FLUSH installation • Low Profile Metal Covers, Steel Bracket



Arlington's new FLB4364 series

DROP IN™ FLOOR BOX KITS are the fastest way to install a box, flush in an EXISTING floor.

Designed for TIME-SAVINGS and a neat, flush installation, DROP IN Box, **now with a plated steel bracket**, installs in MINUTES with a SINGLE hole saw.

DROP IN Box accommodates most 4" covers and comes with a gasketed brass or nickel-plated brass cover. The cover seats into the matching low profile, .040" thick **plated steel bracket**, sitting flush with the floor and reducing trip hazards.



- Gasketed metal covers in brass or nickel-plated brass with flip lids that keep water out, protect the box
- Matching metal carpet ring covers cut carpet ends for a neater finish



**SOLD SEPARATELY** 



Patent pending

# Arlington

1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646

www.aifittings.com



### Low Profile Metal Cover & Bracket • FASTEST Floor Box Installation



CATALOG NUMBER	UPC/DCI/NAED MFG. #018997	DESCRIPTION DROP IN BOX w Plated Steel Bracket	UNIT/STD PKG			
DROP IN™ BOX KITS with METAL COVER WITH TWO FLIP LIDS						
FLB4364MB	22084	Non-metallic box, Brass cover w flip lids	1			
FLB4364NL	22085	Non-metallic box, NIckel-plated brass cover w flip lids	1			
with Ground Clip (Canada)						
FLB4364MB	<b>GC</b> 22096	Non-metallic box, Brass cover w flip lids	1			
FLB4364NLC	<b>C</b> 22097	Non-metallic box, NIckel-plated brass cover w flip lids	1			

DROP IN BOX Kits with .040" thick PLATED STEEL BRACKET include non-metallic box, round 4" diameter metal cover with two flip lids, non-metallic gasket support plate, gasket, UL Listed 15 amp tamper-resistant duplex receptacle, mounting bracket, NM94 and NM95 cable connectors, (3) #8 x 1/2" flathead screws and (1) #6 x 1/2" screw.







FLB4364NL

#### **Installs with a Single Hole Saw**

Flush Installation FAST!

FLB4364MB



1 Determine box location (avoid structural framing members). Use a hole saw to cut a 4-1/4" diameter opening through the floor and subfloor.



2 Insert mounting bracket, using indicator marks to align bracket for proper receptacle orientation. Tighten (3) wing screws to secure bracket to floor.



3 Pull cable. Install in box with supplied cable connector. Attach box to bracket with (3) #8 x 1/2" sheet metal screws (supplied) through the U-shaped cut outs in the box flange.




4 Wire receptacle. Install in box. Attach supplied gasket support plate to receptacle with #6 x 1/2" screw.



5 Cover Installation Install gasket. Attach cover to box with (3) supplied #8 x 1/2" flathead machine screws.



CATALOG NUMBER	WFG. #018997	OVERSIZED METAL CARPET RING	FINISH	UNIT/STD PKG				
CARPET RINGS for FLB4364 Series DROPIN™ BOX								
FLB45CRME	22088	6" diameter. Covers cut ends of carpet	Brass plated	1				
FLB45CRNL	22089	6" diameter. Covers cut ends of carpet	Nickel-plated	1				







Distributed by		



1 Stauffer Industrial Park Scranton, PA 18517

800/233.4717

Fax 570/562.0646 www.aifittings.com