



Powering Business Worldwide

pe.eaton.com

7-function universal TR series timing relay

TRL27

UPC:786685313597

Dimensions:

- **Height:** 3.43 IN
- **Length:** 2.56 IN
- **Width:** 1.38 IN

Weight:3.5 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Contact Configuration:** DPDT
- **Enclosure:** IP40
- **Enclosure Material:** Self-extinguishing plastic
- **Functions:** ON/OFF delay, power triggered, single shot leading or trailing edge voltage controlled and control input, flasher-pause first, ON delay control signal start, trailing edge OFF
- **Input Voltage:** 12-240 Vac/dc
- **Mounting:** Compact DIN rail mount
- **Series:** TR series
- **Time Delay:** 0.05 seconds-100 hours

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [TRL27 Installation Instructions](#)
- [Eaton Specification Sheet - TRL27](#)

Certifications:

- CSA Certified
- cULus Listed



Product compliance:

- CE Marked
- TUV

© 2016 Eaton. All rights reserved.