

Catalog Number: U3990-XL-200

Item Description: 200A 4T RL OU MAIN

784572139336

Brand Name: Milbank

Type: Ringless Meter Socket

Application: Meter Socket With Main

Standard: UL Listed

Voltage Rating: Up to 240 Volts Alternating Current

UPC Code:

Amperage Rating: 200 Ampere Continuous

Phase: 1 Phase

Frequency Rating: 60 Hertz

Number Of Cutouts: 1

Cutout Size: 200 Ampere Main Breaker

Cable Entry: Overhead and Underground

Terminal: Lay in Line Side and Single Mechanical

Load Side

Mounting: Surface Mount

Enclosure: Type 3R, G90 Galvanized Steel with

Powder Coat Finish


Additional Specifications: Number of Jaws:4 Terminal

Hub Opening and Closing Plates:Small Closing Plate


Bypass Provision: No Bypass

Number Positions: 1 Position





FEATURE TABLE		
ITEM	QTY	DESCRIPTION
Α	8	U/L MNTG.EMBOSS
В	1	1/4 SOLID K.O.
С	1	14, 1/2 CONC. K.O.
D	4	11/4, 11/2, 2, 21/2 CONC. K.O.
Е	3	11/4, 11/2, 2, 21/2, 3 CONC, K.O.





Version:

All dimensions are +/- 1/16". Drawing views are not to scale. Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.