MYERS® HR Series Convertible Jet Pumps

Myers® HR Series jet pumps provide reliable service for many residential homes and farms, as well as commercial and industrial applications.

APPLICATIONS

 Supply water systems and sprinkling systems for homes, farms and industry

SPECIFICATIONS

- Cast iron pump case
- Dual compartment, 115/230 Volt double-ball bearing motor with voltage selector switch
- Priming screen
- Diffuser with stainless steel wear ring
- Square D pressure switch



FEATURES

Quality Construction – Durable machined heavy-duty construction pump body provides long product life

Impellers – Precision molded impellers and diffuser provide smooth, balanced performance and efficiency

Pressure Switch – High quality proven pressure switch with adjustable on/off pressure settings. 20 PSI differential.

Motor – Heavy-duty motor with double ball bearing design and voltage selection device

Shaft Seal – Mechanical shaft seal with ceramic face and stainless steel construction for long seal life


ORDERING INFORMATION – SHALLOW WELL						
Catalog		Discharge Pressure	Capac	ity in U.S. Gallons pe Suction Lift in Feet	Shut-Off	
Number	HP	in Lbs.	5	15	20	PSI
HR50S	1/2	20 30 40 50	11.5 11.5 10.5 5.5	9 9 7.5 3.5	6 6 5 2	70

ORDERING INFORMATION - DEEP WELL												
Catalog		Pressure Switch	Average Regulator	Jet Package Cat. Number			Capacity in U.S. Gallons per Minute					
						Packer for	Distance to Low Water Level in Feet					
Number	HP	Setting	Setting	Cast Iron	Bronze	2" Well	30	40	50	60	70	80
HR50D	1/2	20/40 30/50	22 22	DW50-1 DW50-1	DW50 DW50	P50 P50	10 9.5	8 7.5	7 6.5	5.5 5	4.5 4	3.5 3.5




MYERS® HR Series Convertible Jet Pumps

OUTLINE DIMENSIONS



Dimensions (in inches) are for estimating purposes only.

PUMP PERFORMANCE



Repair Parts Kit for HR Series				
Kit Includes				
PK50	Shaft seal, impeller, diffuser, gasket, O-ring, venturi, and nozzle			

