



FIG. 7060

Tee



Cast



Fabricated

FIGURE 7060 TEE

Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	2 1/4 C	0.9
25	33.4	57	0.4
1 1/4	1.660	2 3/4 C	1.5
32	42.2	70	0.7
1 1/2	1.900	2 3/4 C	1.8
40	48.3	70	0.8
2	2.375	3 1/4 C	2.4
50	60.3	83	1.1
2 1/2	2.875	3 3/4 C	4.0
65	73.0	95	1.8
3 O.D.	2.996	4 C	4.6
76.1	76.1	101	2.1
3	3.500	4 1/4 C	5.8
80	88.9	108	2.6
3 1/2	4.000	4 1/2 C	9.8
90	101.6	114	4.4
4 1/4 O.D.	4.250	4 3/4 C	9.3
108.0	108.0	121	4.2
4	4.500	5 C	10.3
100	114.3	127	4.7
5 1/4 O.D.	5.236	5 1/4 C	14.1
133.0	133.0	133	6.4
5 1/2 O.D.	5.500	5 1/2 C	16.1
139.7	139.7	140	7.3
5	5.563	5 1/2 C	16.2
125	141.3	140	7.3
6 1/4 O.D.	6.259	6 C	20.8
159.0	159.0	152	9.4
6 1/2 O.D.	6.500	6 1/2 C	24.4
165.1	165.1	165	11.1
6	6.625	6 1/2 C	25.7
150	168.3	165	11.7
8	8.625	7 3/4 C	41.1
200	219.1	197	18.6
10	10.750	9 C	74.5
250	273.1	229	33.8
12	12.750	10 C	94.7
300	323.9	254	43.0
14	14.000	11	118.0
350	355.6	279	53.5
16	16.000	12	146.0
400	406.4	305	66.2
18	18.000	15 1/2	218.0
450	457.2	394	98.9
20	20.000	17 1/4	275.0
500	508.0	438	125
24	24.000	20	379.0
600	609.6	508	172

C - Cast malleable or ductile iron, all others are fabricated steel.

See Fitting Size chart on page 50 for O.D.



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

FIG. 7076

Gr x Thd

Concentric Reducers




FIGURE 7076 CONCENTRIC REDUCER— GROOVE BY THREAD

Nominal Size	End to End	Approx. Wt. Ea.	Nominal Size	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	Lbs./Kg	In./DN(mm)	In./mm	Lbs./Kg
1 1/2 x 1	2 1/2	0.6	3 1/2 x 3	3	1.8
40 x 25	64	0.3	90 x 80	76	0.8
2 x 3/4	2 1/2	1.0	4 x 1	3	2.2
50 x 80	64	0.5	100 x 25	76	1.0
2 x 1	2 1/2	0.8	4 x 1 1/2	3	2.3
50 x 25	64	0.4	100 x 40	76	1.0
2 x 1 1/4	2 1/2	1.3	4 x 2	3	2.3
50 x 32	64	0.6	100 x 50	76	1.0
2 x 1 1/2	2 1/2	1.3	4 x 2 1/2	3	2.3
50 x 40	64	0.6	100 x 65	76	1.0
2 1/2 x 1	2 1/2	1.0	4 x 3	3	2.6
65 x 25	64	0.5	100 x 80	76	1.2
2 1/2 x 1 1/4	2 1/2	1.0	4 x 3 1/2	3	2.5
65 x 32	64	0.5	100 x 90	76	1.1
2 1/2 x 1 1/2	2 1/2	1.3	5 x 4	3 1/2	4.5
65 x 40	64	0.6	125 x 100	89	2.0
2 1/2 x 2	2 1/2	1.2	6 x 1	4	6.0
65 x 50	64	0.5	150 x 25	102	2.7
3 x 3/4	2 1/2	1.2	6 x 2	4	6.0
80 x 80	64	0.5	150 x 50	102	2.7
3 x 1	2 1/2	1.2	6 x 3	4	6.0
80 x 25	64	0.5	150 x 80	102	2.7
3 x 1 1/2	2 1/2	1.3	6 x 4	4	5.9
80 x 40	64	0.6	150 x 100	102	2.7
3 x 2	2 1/2	1.3	6 x 5	4	5.8
80 x 50	64	0.6	150 x 125	102	2.6
3 x 2 1/2	2 1/2	1.5			
80 x 65	64	0.7			

All are Fabricated Steel.

See Fitting Size chart on page 50 for O.D.

PROJECT INFORMATION

APPROVAL STAMP

Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	