

UL/CSA LISTED POWER FUSES

AMP-TRAP® AG FUSES FIT RIGHT INTO A WIDE VARIETY OF INDUSTRIAL APPLICATIONS



The Mersen Amp-Trap AG fuse series is a complete line of Class G fuses. AG fuses safely fit a wide variety of applications. Class G fuses are made in four physical sizes and provide superior branch-circuit protection for lighting, heating, and appliance circuits.

FEATURES/BENEFITS:


- Four unique sizes from ½-60 amperes do not allow inter-changeability with other fuse classes
- Fiberglass bodies provide dimensional stability in harsh industrial settings

CATALOG NUMBERS (AMPS)

| AG1/2 | AG2 | AG5 | AG10 | AG25 | AG40 | AG50 |
|---------|-----|-----|------|------|------|------|
| AG1 | AG3 | AG6 | AG15 | AG30 | AG45 | AG60 |
| AG1-1/2 | AG4 | AG8 | AG20 | AG35 | | |

DIMENSIONS

| Ampere | Α . | | В | | C . | |
|---------|------|------|------|------|-----|-----|
| Rating | in | mm | in | mm | in | mm |
| 1/2-15A | 1.31 | 33.3 | .406 | 10.3 | .28 | 7.1 |
| 20A | 1.41 | 35.8 | .406 | 10.3 | .28 | 7.1 |
| 25, 30A | 1.62 | 41.2 | .406 | 10.3 | .28 | 7.1 |
| 35-60A | 2.25 | 57.2 | .406 | 10.3 | .50 | |



Cross Reference: AG will replace the following fuses: Bussmann SC, Littelfuse SLC

RATINGS:

- **Volts:** 600VAC (1/2 to 20A), 480VAC (25 to 60A)
- **Amps:** 1/2 to 60A
- IR: 100kA I.R. AC

HIGHLIGHTS:

- Current-limiting
- Time-delay (above 5A)

APPLICATIONS:

- Lighting
- Heating*
- Appliances

*except in Canada where fuses must be "P" or "D" type.

APPROVALS:

- UL listed to standard 248-5 File E2137
- CSA certified to standard C22.2 No. 248.5



